



PLATINUM MaxExpert C3 5W-40

Quality class: API: SN/SM/CF

ACEA: C3

Viscosity grad: SAE: 5W-40

GENERAL FEATURES:

Synthetic engine oil based on the Complex Protection Formula. CPF ensures optimum engine protection under all operating conditions. It reduces the risk of wear in valves by providing better control of deposits, thus contributing to reduction of particulate matter deposits on DPF filters and diminishing the risk of poisoning the catalyts in spark-ignition engines.

It guarantees:

- Effective lubrication of engines with unit injectors,
- Environmental protection,
- Engine cleanliness maintained by keeping soot in suspension,
- Easy engine start in cold conditions.

APPLICATION:

Platinum MaxExpert C3 5W-40 is designed for year-round operation in modern engines, passenger cars and light commercial vehicles, mainly Volkswagen Group diesel engines (Volkswagen, Audi, Skoda, Seat) fitted with injection system based on unit injectors. It is also suitable for use in petrol engines under various operating conditions in both summer and winter.

Platinum MaxExpert C3 5W-40 is compatible with exhaust gas treatment devices such as: DPF and TWC. Recommended for vehicles that meet the Euro 6 standard.

STANDARDS, APPROVALS. SPECIFICATION:

Approvals:

MB-Approval 229.31
VW 502 00/505 00/505 01

Meets the requirements of:

Mercedes-Benz 226.5
Renault RN0700/0710
Porsche A40



Ford WSS-M2C917A
General Motors GM Dexos 2

PARAMETERS	UNIT	TYPICAL VALUES
SAE viscosity class	-	5W-40
Kinematic viscosity at 100°C	mm ² /s	14.0
Viscosity indicator	-	169
Pour point	°C	-42
TBN number	Mg KOH/g	8.0

NOTE:
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

