



PLATINUM ULTOR DIESEL 20W-50

Quality class: API: CF-4/CF/SJ
Viscosity grad: SAE: 20W-50

GENERAL FEATURES:

Multi-grade oil designed primarily for use in trucks, buses and heavy machinery with diesel engines.

Guarantee: - Engine protection at the critical moment, the cold start; - Keeping engine clean during the operation; - Maintained high lubricating properties between oil changes.

APPLICATION:

PLATINUM ULTOR DIESEL 20W-50 is designed primarily for use in trucks, buses and heavy machinery with diesel engines. It can be successfully applied for constructions operated in extreme load conditions.

It is suitable for use in engines meeting the Euro II standard.

STANDARDS, APPROVALS. SPECIFICATION:

Meet requirements:

Mercedes-Benz 228.0 Mercedes-Benz 228.1 MAN 270 MAN 271 MTU 1.0 DEUTZ DQC-I-05

PARAMETERS	UNIT	TYPICAL VALUES
SAE viscosity grade	-	20W-50
Kinematic viscosity at 100°C	mm ² /s	17,1
Viscosity index	-	121
Flow temperature	°C	-27
TBN base number	Mg KOH/g	8,0
Sulphide ash	%	1,0

NOTE:
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

