SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)



SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : TRANSLUBE Product code : 74100

1.2. Relevant identified uses of the substance or mixture and uses advised against

Transmission oil

1.3. Details of the supplier of the safety data sheet

Registered company name : MOTUL Address : 119, Boulevard Felix Faure. 93300 AUBERVILLIERS CEDEX FRANCE Telephone : 33.1.48.11.70.00. Fax: 33.1.48.33.28.79. Telex: . Email : motul_hse@motul.fr

1.4. Emergency telephone number : +44 (0) 1235 239 670.

Association/Organisation : ORFILA.

Other emergency numbers

BRAZIL : +55 11 3197 5891 / COLOMBIA : +57 1 508 7337 / ARGENTINA : +54 11 5984 3690 / CHILE : +562 2582 9336 Ireland : +353 1 8092566 UNITED STATES: 001 866 928 0789 / CANADA: 001 800 579 7421 / MEXICO : +52 55 5004 8763 / MIDDLE EAST - AFRICA : +44 1235 239671 24 heure a day: 7 days a week

24 hours a day, 7 days a week

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

May produce an allergic reaction (EUH208).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Additional labeling	:
EUH208	Contains LONG CHAIN ALKYL AMINE
	. May produce an allergic reaction.
Hazard statements	:
H412	Harmful to aquatic life with long lasting effects.
Precautionary state	ements - General :
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
Precautionary state	ements - Prevention :
P273	Avoid release to the environment.
Precautionary state	ements - Disposal :
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 64742-54-7		L	50 <= x % < 100
EC: 265-157-1			
REACH: 01-2119484627-25			

DISTILLATES (PETROLEUM),			
HYDROTREATED HEAVY PARAFFINIC			
CAS: 64742-57-0		L	10 <= x % < 25
		L	10 <= X % < 25
EC: 265-160-8			
REACH: 01-2119489287-22-0004			
RESIDUAL OILS (PETROLEUM),			
HYDROTREATED			
CAS: 64742-65-0	GHS08	L	1 <= x % < 2.5
EC: 265-169-7	Dgr		
	Asp. Tox. 1, H304		
DISTILLATES (PETROLEUM),			
SOLVENT-DEWAXED HEAVY			
PARAFFINIC			
CAS: 64742-54-7		L	1 <= x % < 2.5
EC: 265-157-1			1 - 7/0 - 2.0
REACH: 01-2119484627-25			
NERGH. 01-2113404021-23			
DISTILLATES (PETROLEUM),			
HYDROTREATED HEAVY PARAFFINIC			
			0 <= x % < 1
EC: 701-175-2	GHS06, GHS05, GHS09		0 <= x % < 1
REACH: 01-2119456798-18	Dgr		
	Acute Tox. 4, H302		
LONG CHAIN ALKYL AMINE	Acute Tox. 3, H311		
	Skin Corr. 1B, H314		
	Skin Sens. 1A, H317		
	Eye Dam. 1, H318		
	Acute Tox. 1, H330		
	STOT SE 3, H335		
	Aquatic Acute 1, H400		
	M Acute = 1		
	Aquatic Chronic 1, H410		
	M Chronic = 1		
CAS: 1213789-63-9	GHS07, GHS05, GHS09, GHS08		0 <= x % < 1
EC: 627-034-4	Dgr		
REACH: 01-2119473797-19	Acute Tox. 4, H302		
	Asp. Tox. 1, H304		
(Z)-OCTADEC-9-ENYLAMINE,	Skin Corr. 1B, H314		
C16-18-(EVEN NUMBERED,	Eye Dam. 1, H318		
SATURATED AND	STOT SE 3, H335		
UNSATURATED AND UNSATURATED)-ALKYLAMINES	STOT RE 2, H373		
UNGATUNATED -ALICI LAWIINES			
	Aquatic Acute 1, H400 M Acute = 10		
	Aquatic Chronic 1, H410 M Chronic = 10		
	100000 = 10		

(Full text of H-phrases: see section 16)

Information on ingredients :

Note L: The carcinogen classification does not apply because the substance contains less than 3 % w/w of dimethyl sulphoxide (DMSO) measured using the IP 346 method.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor. NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

Remove the victim to fresh air. If the symptoms persist, call a physician.

In the event of splashes or contact with eyes :

Wash immediately and abundantly with water, including under the eyelids.

In the event of splashes or contact with skin :

In the event of an allergic reaction, seek medical attention.

Immediately remove all soiled clothing.

Wash immediately and abundantly with soap and water.

In the event of swallowing :

Seek medical attention, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

Dry agent, foam, carbon dioxide.

Unsuitable methods of extinction

High volume water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO2)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

Spilled product may make surfaces slippery.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Avoid contact with eyes.

No special precaution apart from the observance of hygiene rules

Fire prevention :

Prevent access by unauthorised personnel.

Take precautionary measures against static discharges by bonding and grounding equipment.

No smoking.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) TRANSLUBE - 74100

Ensure good ventilation at the workplace

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used. Do not breathe fumes, vapour, spray.

7.2. Conditions for safe storage, including any incompatibilities

Store between 5° C and 40° C in a dry, well ventilated place. Only use hydrocarbon-resistant containers, joints and pipes.

Storage

Keep out of reach of children.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No data available.

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

RESIDUAL OILS (PETROLEUM), HYDROTREATED (CAS: 64742-57-0)Final use:Workers.Exposure method:Inhalation.Potential health effects:Long term local effects.DNEL :5.4 mg de substance/m3

Final use:

Exposure method: Potential health effects: DNEL :

Predicted no effect concentration (PNEC):

LONG CHAIN ALKYL AMINE

Environmental compartment:	Fresh water.
PNEC :	0.001 mg/l

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction. Personnel shall wear regularly laundered overalls.

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained. Store personal protective equipment in a clean place, away from the work area. Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

Consumers.

Long term local effects.

1.2 mg de substance/m3

Inhalation.

Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374. Gloves must be selected according to the application and duration of use at the workstation. Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required. Type of gloves recommended :

Glove	0.38 mm
thickness:	
Break-through	> 480 mn
timo:	

time:

6

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Breathing apparatus only when aerosol or spray are formed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state :		Fluid liquid.
Color:		Amber
Important health, s	safety and environmental information	
pH :		Not relevant.
Flash Point Interval :		FP > 100°C.
Vapour pressure (50°	C) :	Not relevant.
Density :		>1
Water solubility :		Insoluble.
Viscosity :		145 mm²/s à 40°C

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Keep away from heat and from sources of ignition

Take precautionary measures against static discharges.

10.5. Incompatible materials

Strong oxidants

Acids

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

No data available.

11.1.1. Substances

Acute toxicity :

LONG CHAIN ALKYL AMINE

Inhalation route (n/a) :

LC50 = 17.9 mg/l Species : Rat

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS: 64742-65-0) Oral route : LD50 > 5000 mg/kg

ETY DATA SHEET (REGULATION (EC) n° NSLUBE - 74100	1907/2006 - REACH) Version 10.1 (10-01-	2020) Tage 0/
	Species : Rat	
Dermal route :	LD50 > 5000 mg/kg	
Demanoule.	Species : Rabbit	
Inhalation route (n/a) :	LC50 > 5 mg/l	
RESIDUAL OILS (PETROLEUM), HYDRO		
Oral route :	LD50 > 5000 mg/kg	
	Species : Rat	
	OCDE Ligne directrice 420 (Toxicité orale aiguë - Méthode de la dos	e
	prédéterminée)	
Dermal route :	LD50 > 5000 mg/kg	
	Species : Rabbit	
	OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)	
Inhalation route (n/a) :	LC50 > 5 mg/l	
	Species : Rat	
	OCDE Ligne directrice 403 (Toxicité aiguë par inhalation)	
DISTILLATES (PETROLEUM), HYDROTR	REATED HEAVY PARAFFINIC (CAS: 64742-54-7)	
Oral route :	LD50 > 5000 mg/kg	
	Species : Rat	
	OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)	
Dermal route :	LD50 > 5000 mg/kg	
	Species : Rabbit	
	OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)	
Inhalation route (n/a) :	LC50 > 5 mg/l	
	Species : Rat	
1.1.2. Mixture		
kin corrosion/skin irritation :		
Repeated or prolonged contact with the prepaborption through the skin.	paration may cause removal of natural fat from the skin resulting in non allergic co	ntact dermatitis a
erious damage to eyes/eye irritation :		
Mild eye irritation		
espiratory or skin sensitisation :		
	. May cause an allergic reaction.	
Contains at least one sensitising substance.		
Contains at least one sensitising substance. spiration hazard :		
spiration hazard :	of the respiratory system in very susceptible persons."	
spiration hazard :	of the respiratory system in very susceptible persons."	
spiration hazard : "Inhalation of vapours may cause irritation o May cause lung damage if swallowed		
 Spiration hazard : "Inhalation of vapours may cause irritation of May cause lung damage if swallowed CTION 12 : ECOLOGICAL INFORMATION 	ION	
spiration hazard : "Inhalation of vapours may cause irritation o May cause lung damage if swallowed	ION cts.	
spiration hazard : "Inhalation of vapours may cause irritation of May cause lung damage if swallowed CTION 12 : ECOLOGICAL INFORMATI Harmful to aquatic life with long lasting effect The product must not be allowed to run into	ION cts.	
 Spiration hazard : "Inhalation of vapours may cause irritation of May cause lung damage if swallowed CTION 12 : ECOLOGICAL INFORMATION Harmful to aquatic life with long lasting effect The product must not be allowed to run into 2.1. Toxicity 	ION cts.	
spiration hazard : "Inhalation of vapours may cause irritation of May cause lung damage if swallowed CTION 12 : ECOLOGICAL INFORMATI Harmful to aquatic life with long lasting effect The product must not be allowed to run into 2.1. Toxicity 2.1.1. Substances	ION cts. o drains or waterways.	213789-63-9)
 spiration hazard : "Inhalation of vapours may cause irritation of May cause lung damage if swallowed CTION 12 : ECOLOGICAL INFORMATION Harmful to aquatic life with long lasting effect The product must not be allowed to run into 2.1. Toxicity 2.1.1. Substances (Z)-OCTADEC-9-ENYLAMINE, C16-18-(EX) 	TION cts. 9 drains or waterways. VEN NUMBERED, SATURATED AND UNSATURATED)-ALKYLAMINES (CAS: 12	213789-63-9)
spiration hazard : "Inhalation of vapours may cause irritation of May cause lung damage if swallowed CTION 12 : ECOLOGICAL INFORMATI Harmful to aquatic life with long lasting effect The product must not be allowed to run into 2.1. Toxicity 2.1.1. Substances	ION cts. o drains or waterways.	213789-63-9)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC (CAS: 64742-54-7) Fish toxicity : LC50 > 100 mg/l Duration of exposure : 96 h

Crustacean toxicity :

2

2

EC50 > 10000 mg/l Duration of exposure : 48 h

TRANSLUBE - 74100	
	NOEC > 10000 mg/l
	Species : Daphnia magna
	OCDE Ligne directrice 211 (Daphnia magna, essai de reproduction)
	OCDE Lighe directice 211 (Daphina magna, essai de reproduction)
Algae toxicity:	ECr50 > 100 mg/l
Algae toxicity :	Duration of exposure : 72 h
	Duration of exposure . 72 fr
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED	
	LC50 > 100 mg/l
Fish toxicity :	-
	Species : Pimephales promelas
	Duration of exposure : 96 h
Crustagen tovisity	
Crustacean toxicity :	EC50 > 1000 mg/l
	Species : Daphnia magna
	Duration of exposure : 48 h
	NOEC = 10 mg/l
	Species : Daphnia magna
	Duration of exposure : 21 jours
Algae toxicity :	ECr50 > 100 mg/l
	Species : Pseudokirchnerella subcapitata
	Duration of exposure : 72 h
	NOEC = 100 mg/l
	Species : Pseudokirchnerella subcapitata
	Duration of exposure : 72 h
RESIDUAL OILS (PETROLEUM), HYDROTREATED (
Fish toxicity :	LC50 > 100 mg/l
	Species : Oncorhynchus mykiss
	Duration of exposure : 96 h
	OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)
	NOEC > 1000 mg/l
	Species : Oncorhynchus mykiss
	Duration of exposure : 14 jours
Crustacean toxicity :	EC50 > 10000 mg/l
	Species : Daphnia magna
	Duration of exposure : 48 h
	OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)
	NOEC = 10 mg/l
	Species : Daphnia magna
	Duration of exposure : 21 jours
	OCDE Ligne directrice 211 (Daphnia magna, essai de reproduction)
Algae toxicity :	ECr50 > 100 mg/l
	Species : Pseudokirchnerella subcapitata
	Duration of exposure : 48 h
	OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)
12.1.2. Mixtures	
No aquatic toxicity data available for the mixture.	
12.2. Persistence and degradability	
12.2.1. Substances	
	ERED, SATURATED AND UNSATURATED)-ALKYLAMINES (CAS: 1213789-63-9)
Biodegradability :	no degradability data is available, the substance is considered as not
Dioucyrauability.	
	degrading quickly.

LONG CHAIN ALKYL AMINE

7

Biodegradability :	no degradability data is available, the substance is considered as not degrading quickly.
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED Biodegradability :	HEAVY PARAFFINIC (CAS: 64742-65-0) no degradability data is available, the substance is considered as not degrading quickly.
RESIDUAL OILS (PETROLEUM), HYDROTREATED (Biodegradability :	CAS: 64742-57-0) no degradability data is available, the substance is considered as not degrading quickly.
DISTILLATES (PETROLEUM), HYDROTREATED HE	AVY PARAFFINIC (CAS: 64742-54-7)
Biodegradability :	Rapidly degradable.
12.3. Bioaccumulative potential	
12.3.1. Substances	
DISTILLATES (PETROLEUM), HYDROTREATED HE/	AVY PARAFFINIC (CAS: 64742-54-7)
Octanol/water partition coefficient :	log Koe > 6

12.4. Mobility in soil

Not very mobile in soil.

The product is insoluble in water and will spread on the surface

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

Do not dispose of the product in the natural environment, effluents or surface waters.

German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 2 : Hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container. Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

- 14.1. UN number
- 14.2. UN proper shipping name
- 14.3. Transport hazard class(es)
- •
- 14.4. Packing group
- -

_

- 14.5. Environmental hazards
- -
- 14.6. Special precautions for user
- -

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture


- Classification and labelling information included in section 2:
 - The following regulations have been used:
 - EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/1480 (ATP 13)
 - EU Regulation No. 1272/2008 amended by EU Regulation No. 2019/521 (ATP 12)
 - Container information:

No data available.

- Particular provisions :

No data available.

- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) : WGK 2 : Hazardous for water.
 - Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) : NFPA 704, Labelling: Health=0 Inflammability=1 Instability/Reactivity=1 Specific Risk=none



15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.