



RAVENOL CVTF NS3/J4 Fluid



ART.-NR. 1211132

1 L | 1211132-001
4 L | 1211132-004
20 L | 1211132-020
20 L | 1211132-B20
208 L | 1211132-208
208 L | 1211132-D28
1000 L | 1211132-700

FABRICATION SYNTHETIC

RECOMMENDATIONS NISSAN KLE53-00002 | NISSAN KLE53-00004 | NISSAN 999MP-NS300P | NISSAN ATF NS-3 | MITSUBISHI MZ320261 | MITSUBISHI MZ320262 | MITSUBISHI MZ320288 | MITSUBISHI MZ102658 | MITSUBISHI ATF J4 | SUZUKI CVT FLUID GREEN 2 9900022B24046 | SUZUKI CVT FLUID GREEN 2 990N022B24004

RAVENOL CVTF NS3/J4 Fluid is a synthetic CVTF (Continuously *Variable* Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the CVT transmission.

RAVENOL CVTF NS3/J4 Fluid is a CVTF of the latest generation. It is especially developed for the CVT transmission of JATCO. It guarantees in any mode for maximum wear protection.

RAVENOL CVTF NS3/J4 Fluid is green colored.

Application Notes

RAVENOL CVTF NS3/J4 Fluid is suitable for use in CVT transmission of following vehicles:

Nissan Qashqai J11 2013-, Nissan Pathfinder R52 2013-, Nissan Altima L33 2013-, Nissan Teana L33 2013-, Nissan Sylphe B17 2012-, Nissan Tiida C12 2014-, Nissan X-Trail T32 2013-, Nissan Elgrand E52 2013-, Nissan Murano Z51 2013-, Nissan Murano Z52 2015-, Mitsubishi Outlander GF7W/8W 2012-, Mitsubishi Delica D5 2012-, Mitsubishi Lancer 2012-, Mitsubishi ASX 2014-, Renault Koleos 2014-, Samsung QM5 2013-, Peugeot 4008 2014-, Citroen C4 Aircross 2014- and others with CVT-transmission JATCO JF016E or JF017E.

Maintenance-filling under normal operating conditions.

Characteristics

RAVENOL CVTF NS3/J4 Fluid offers:

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- A high thermal and oxidative stability
- An excellent cooling capacity



RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult

our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to

malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission. Ravensberger

Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	836,0	EN ISO 12185
Colour		grün	visual
Pourpoint	°C	-57	DIN ISO 3016

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 10. March 2020