



RAVENOL Getriebeoel EPX SAE 80W-90 GL 5



VISCOSITY 80W-90

SPECIFICATIONS API GL-5

FABRICATION MINERAL

APPROVALS ZF TE-ML 16B | ZF TE-ML 19B | ZF TE-ML 17B | ZF TE-ML 21A | LOVAT LOV-204

RECOMMENDATIONS MIL-L-2105 D | MB 235.0 | MAN 342 TYP M1 | FORD SQM-2C-9002 AA

ART.-NR. 1223205

1 L	1223205-001
4 L	1223205-004
10 L	1223205-010
20 L	1223205-020
20 L	1223205-B20
208 L	1223205-208
208 L	1223205-D28
1000 L	1223205-700

Multigrade hypoid transmission oil for synchronised and not synchronised manual transmissions as well as axle drives, distributor transmissions, intermediate transmissions in vehicles and working machines.

In order to avoid the seasonal change of the transmission oil **RAVENOL Getriebeoel EPX SAE 80W-90 GL 5** was developed. It can be used in winter as well as in summer. Its universal use reduces the risk of mix-up and storage.

RAVENOL Getriebeoel EPX SAE 80W-90 GL 5 guarantees due to the balanced additive combination characteristics like a high pressure absorption capacity, a superior viscosity temperature behaviour, a high oxidation stability, low pour points, a good corrosion protection and non-sludging.

Application Notes

RAVENOL Getriebeoel EPX SAE 80W-90 GL 5 is compatible with all brand-name transmission oils. In case of changing to **RAVENOL Getriebeoel EPX SAE 80W-90 GL 5** flushing is not necessary.

RAVENOL Getriebeoel EPX SAE 80W-90 GL 5 can be used in manual transmissions, axle drives, distributor and intermediate transmissions in vehicles and working machines.

Characteristics

RAVENOL Getriebeoel EPX SAE 80W-90 GL 5 offers:

- Optimal cold flow property.
- Outstanding wear protection even with short trips in winter.
- High pressure stable lubrication film, thus outstanding wear protection under any stress
- Reduced transmission noise and the best transmission efficiency under full load, i.e. even with very hot oil.
- Outstanding shearing stability
- Excellent oxidation stability, no foaming
- No oil thickening or deposits
- Extraordinary ageing stability



- Excellent viscosity-temperature properties
- Effective wear protection
- Extraordinary corrosion protection, no rust, won't harm non-ferrous metals
- Neutral to sealants, transmissions stay tight, no oil loss

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	882,0	EN ISO 12185
Colour		braun	visual
Viscosity at 100°C	mm ² /s	14,1	DIN 51562-10
Viscosity at 40°C	mm ² /s	140,5	DIN 51562-10
Viscosity index VI		97	DIN ISO 2909
Brookfield Viscosity	mPa*s	69.000	ASTM D 2983
Pourpoint	°C	-33	DIN ISO 3016
Flash point (COC)	°C	200	DIN ISO 2592
Copper Strip Test		1b	ASTM D130

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 05. July 2021