

KeContact P30



OCPP



Product

| | |
|----------------------|---------------------------------------|
| Item number: | 109.651 |
| Product designation: | x-series EN Type2 Socket 22kW-WLAN/4G |
| EAN code: | 9120050712461 |

Specifications

| | |
|--|---|
| Socket: | Type 2 standard socket: 32 A / 400 V AC in accordance with EN 62196-1 and VDE-AR-E 2623-2-2 |
| Power: | 22 kW |
| Energy meter (LED display): | Yes |
| OCPP backend: | Yes |
| Local load management: | Master |
| Current monitoring: | Depending on the charging cable dimensions |
| UDP: | Yes |
| External meter (integration through Modbus): | Yes |
| Color: | RAL 7004 (signal gray) / RAL 7016 (anthracite gray) |

General

| | |
|--|--|
| Charge mode: | Mode 3 in accordance with IEC 61851-1 AC charging |
| Overvoltage category: | III in accordance with EN 60664 |
| Protection class: | I |
| Protection class: | IP54 |
| Protection against mechanical impact: | IK08 (except for cylinder lock) |
| Rated short-time withstand current: | < 10 kA (effective value in accordance with EN 61439-1) |
| Residual direct current detecting device (RDC-DD): | > 6 mA (characteristic in accordance with IEC 62955, < 10 s) |
| Ventilation during charging: | Not supported |

Power supply

| | |
|--------------------------------|---|
| Rated supply voltage (Europe): | 3 x 230 V / 400 V |
| Internal consumption: | Idling: 4 W, plugged in: 5 W, charging: 7 W |
| Rated current (configurable): | 10 A / 13 A / 16 A / 20 A / 25 A / 32 A 1-phase or 3-phase |
| Line frequency: | 50 Hz |
| Mains forms: | TT / TN / IT |

Supply terminals

| | |
|-------------|----------------------------------|
| Type: | Spring-type terminal |
| Cable feed: | Top (surface), back side (flush) |



KeContact P30

| | |
|--|---|
| Connection cross-section of the supply: | Minimum cross-section (depending on the cable and the type of installation) |
| • 16 A rated current: | 5 x 2.5 mm ² |
| • 32 A nominal current: | 5 x 6.0 mm ² |
| Cross section: | |
| • Rigid / flexible: | 0.2 – 16 mm ² |
| • Flexible with wire end sleeve with / without plastic sleeve: | 0.25 – 10 mm ² |
| AWG: | 24 – 6 |
| Stripping length: | 12 mm |
| Temperature rating: | 105 °C |

Ambient conditions

| | |
|--|---|
| Use: | Inside and outside area |
| Access limitations at set-up location: | Limited and unlimited access |
| Installation (stationary): | On the wall or on a floor-mounted column. |
| Operating temperature: | |
| • 16 A: | -25 °C to +50 °C (without direct sunlight) |
| • 32 A: | -25 °C to +40 °C (without direct sunlight) |
| Storage temperature: | -25 °C to +80 °C |
| Relative air humidity: | 5 % to 95 % (non condensing) |
| Altitude: | max. 2000 m above sea level |
| Rate of temperature change: | max. 0.5 °C / min |
| Temperature behavior: | Automatic power reduction if overheating occurs |

Interfaces



Ethernet interface

| | |
|---------------------|-----------------------------|
| Ethernet1: | LSA+ [®] terminals |
| Data transfer rate: | 10/100/1,000 Mbit/s |
| Ethernet2: | RJ45 (for debug) |



USB interface

| | |
|--------------------|-----------------------|
| Type: | A, USB 2.0 (Hi-Speed) |
| Max. output power: | 500 mA |

Enable input

| | |
|-------------------|---|
| Type: | External, potential-free switch contact |
| Type of terminal: | Spring-type terminal |
| Cross section: | 0.08 – 4 mm ² |
| AWG: | 28 – 12 |
| Stripping length: | 8 mm |

KeContact P30

Switch contact output

| | |
|-------------------------------|---|
| Type: | External safety extra-low voltage, <50 V AC, 50/60 Hz |
| Necessary current limitation: | <0.5 A |
| Type of terminal: | Spring-type terminal |
| Cross section: | 0.08 – 4 mm ² |
| AWG: | 28 – 12 |
| Stripping length: | 8 mm |

Features



4G/LTE mobile network communication

| | |
|------------------|--|
| Supported bands: | 4G with fallback to 3G/2G <ul style="list-style-type: none">LTE (4G) Bands: 1, 3, 8, 20, 28UMTS/HSPA+ (3G) Bands: 1, 8GSM/GPRS/Edge (2G) Dual-band |
| Max. data rate: | LTE CAT 1 Download: 10.2 Mbps* Upload: 5.2 Mbps* *Depends on external influences |
| SIM card: | SIM card with 4G authentication Size: Mini-Sim (2FF) Type: Industrial/M2M recommended |



WLAN / Wifi

| | |
|------------------|-----------------------------|
| Type: | IEEE 802.11 b,g,n, 2.4 GHz |
| Supported modes: | AP Ad-hoc-Mode, Client Mode |

Certifications*

| | |
|-------------------------------|-----|
| CE Declaration of Conformity: | Yes |
|-------------------------------|-----|

* Information about the certifications can be downloaded from the KEBA website:
www.keba.com/emobility-downloads

Dimensions and weight

| | |
|-------------------------|--|
| Height / Width / Depth: | 516 mm / 240 mm / 166 mm |
| Weight: | Approx. 4.8 - 5 kg (depending on device version) |

KeContact P30

