

KeContact P30



Product

Item number:	119.928
Product designation:	a-series EN Type2 3p 6m Cable 11kW-RFID
EAN code:	9120050713666

Specifications

Cable:	Type 2 cable: up to 20A / 400V AC in accordance with EN 62196-1 and VDE-AR-E 2623-2-2
Output:	11 kW
Current monitoring:	No
Color:	RAL 9010 (pure white) / RAL 7016 (anthracite gray)

General

Charge mode:	Mode 3 in accordance with IEC 61851-1 AC charging
Overvoltage category:	III in accordance with EN 60664
Protection class:	I
protection type:	IP54
Protection against mechanical impact:	IK09
Rated short-time withstand current:	< 10 kA (effective value in accordance with EN 61439-1)
Residual direct current detecting device (RDC-DD):	> 6 mA (characteristic in accordance with IEC 62955, < 10 s)
Ventilation:	If ventilation is requested by the vehicle, charging will not be started.

Power supply

Rated supply voltage (Europe):	3 x 230 V / 400 V
Internal consumption:	Idling: 3 W, plugged in: 4.5 W, charging: 6.5 W
Rated current (configurable):	10 A / 13 A / 16 A 1-phase or 3-phase
Line frequency:	50 Hz
Mains forms:	TT / TN / IT

Supply terminals

Type:	Spring-type terminal
Cable feed:	Top (surface), back side (flush)
Connection cross-section of the supply:	Minimum cross-section (depending on the cable and the type of installation)
• 16 A rated current:	5 x 2.5 mm ²
• 32 A nominal current:	5 x 6.0 mm ²
Cross section (cable):	0.2 – 10 mm ²
AWG:	24 – 6
Stripping length:	12 mm
Temperature rating:	105 °C



Ambient conditions

Use:	Inside and outside area
Access limitations at set-up location:	Limited and unlimited access
Installation (stationary):	On the wall or on a floor-mounted column.
Operating temperature:	
• 16 A:	-25 °C to +50 °C (without direct sunlight)
• 32 A:	-25 °C to +40 °C (without direct sunlight)
Storage temperature:	-25 °C to +80 °C
Relative air humidity:	5 % to 95 % (non condensing)
Altitude:	max. 2000 m above sea level
Rate of temperature change:	max. 0.5 °C / min
Temperature behavior:	Automatic power reduction if overheating occurs

Interfaces



Ethernet interface

Ethernet2:	RJ45 (for debug)
------------	------------------



USB interface

Type:	A, USB 2.0 (Hi-Speed)
Max. output power:	500 mA

Enable input

Type:	External, potential-free switch contact
Type of terminal:	Spring-type terminal
Cross section:	0.08 – 4 mm ²
AWG:	28 – 12
Stripping length:	8 mm

Switch contact output

Type:	External safety extra-low voltage, < 50 V AC (50/60 Hz), ≤ 24 V DC
Required current limitation:	< 0.5 A
Terminal type:	Spring-type terminal
Cross section:	0.08 – 4 mm ²
AWG:	28 – 12
Stripping length:	8 mm

Features



RFID card

Type:	MIFARE card / tag according to ISO 14443 or ISO 15693
-------	---

Certifications*

CE Declaration of Conformity:	Yes
-------------------------------	-----

KeContact P30

* Information about the certifications can be downloaded from the KEBA website:
www.keba.com/emobility-downloads

Dimensions and weight

Height / Width / Depth:

643 mm / 240 mm / 142 mm

Weight:

Approx. 5.3 - 7.8 kg (depending on device version)

