

## C. Cable Mode3Typ1/2 32A 3xAWG10 VDE7,5m



Image is for illustration purposes only. Please refer to product description.

Part number	08 91 409 0201 A0
Specification	C. Cable Mode3Typ1/2 32A 3xAWG10 VDE7,5m
HARTING eCatalogue	<a href="https://b2b.harting.com/08914090201A0">https://b2b.harting.com/08914090201A0</a>

### Identification

Element	Charging cable
Specification	Straight
Charging mode	Mode 3
Connector 1	Type 1 Female (Vehicle side)
Connector 2	Type 2 Male (infrastructure side)

### Version

Cable length	7.5 m
Termination method	Crimp termination
Core structure	3x 6 mm <sup>2</sup> + 0.5 mm <sup>2</sup>
Number of phases	1
Number of contacts	5
Number of signal contacts	2
Number of power contacts	3
Contact configuration	Signal: CP, PP Power: L1, N, PE
Details	Also available with customer specific logo on request.

### Technical characteristics

Rated current (signal)	2 A
Rated voltage (signal)	30 V
Rated current (power)	32 A



**Pushing Performance**  
Since 1945

## Technical characteristics

Rated voltage (power)	250 V
Type of current	AC
Charging power	7.2 kW
Coding resistance	220 $\Omega$ between PE and PP
Ambient temperature	-30 ... +50 °C in operation -40 ... +80 °C storage/transport
Air pressure	$\geq 540$ hPa $\approx 5000$ m
Insertion force	<100 N
Withdrawal force	<100 N
Mating cycles	$\geq 10,000$
Degree of protection acc. to IEC 60529	IP44 mated condition
Cable diameter	12.8 mm $\pm$ 0.4 mm
Minimum bending radius	9x Cable diameter (repeated bending)
Conductor resistance @ 20 °C	$\leq 3.3$ $\Omega$ /km @ 6 mm <sup>2</sup> $\leq 39$ $\Omega$ /km @ 0.5 mm <sup>2</sup>

## Material properties

Material (insert)	Polyamide (PA)
Colour (insert)	Black
Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material (hood/housing)	Polyamide (PA)
Colour (hood/housing)	Black
Material (cover)	Thermoplastic polyurethane (TPU)
Material (cable)	Thermoplastic polyurethane (TPU)
Colour (cable)	Black
Material flammability class acc. to UL 94	V-0

## Specifications and approvals

Specifications	IEC 62196-2 IEC 62893
CE	Yes

## Commercial data

Packaging size	1
----------------	---



**Pushing Performance**  
Since 1945

## Commercial data

Net weight	3.5 kg
Country of origin	Romania
European customs tariff number	85444290
eCl@ss	27144705 Charging cable E-Mobility