
0RS311P-2.5L

		OF	RS311P-2.5L			
Date of	compilation: 06/05/2022	Revised: 03/03/2023	Version: 2 (Replaced 1)			
SECT	TON 1: IDENTIFICATIO	N OF THE SUBSTANCE/M	IXTURE AND OF THE COMPANY/UNDERTAKING			
1.1	Product identifier:	0RS311P-2.5L	_			
	Other means of identifi	cation:				
	UFI:	Q3G6-90UU-L	J00W-1JVK			
1.2	Relevant identified use	s of the substance or mixtu	ure and uses advised against:			
	Relevant uses: Hardener f	or coatings. For professional us	sers only.			
	Uses advised against: All u	uses not specified in this sectio	n or in section 7.3			
1.3	Details of the supplier of	of the safety data sheet:				
	Inter Cars S.A. ul. Powsińska 64 02-903 Warszawa - Polska kontakt@intercars.com www.intercars.com					
1.4	Emergency telephone r	umber:				
SECT	TON 2: HAZARDS IDEN	TIFICATION				
2.1	Classification of the sul	ostance or mixture:				
	CLP Regulation (EC) No	1272/2008:				
	Classification of this produ	ict has been carried out in acc	ordance with CLP Regulation (EC) No 1272/2008.			
	Acute Tox. 4: Acute inhalation toxicity, Category 4, H332 Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412 Asp. Tox. 1: Aspiration hazard, Category 1, H304 Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Liq. 3: Flammable liquids, Category 3, H226 Skin Irrit. 2: Skin irritation, Category 2, H315 Skin Sens. 1: Sensitisation, skin, Category 1, H317 STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373 STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336					
2.2	Label elements:					
	CLP Regulation (EC) No	1272/2008:				
	Danger	>				
	Hazard statements:					
	H226 - Flammable liquid a H304 - May be fatal if swa H315 - Causes skin irritati H317 - May cause an aller H319 - Causes serious eye H332 - Harmful if inhaled. H335 - May cause respirat H336 - May cause drowsir	allowed and enters airways. on. rgic skin reaction. e irritation. tory irritation.				
		e to organs through prolonged life with long lasting effects.	or repeated exposure (Oral).			

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements:

PROFIRS



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation



0RS311P-2.5L

Date of compilation: 06/05/2022 Revised:

Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 2: HAZARDS IDENTIFICATION (continued)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

EUH204: Contains isocyanates. May produce an allergic reaction.

Substances that contribute to the classification

Hexamethylene diisocyanate, oligomers; 2-butoxyethyl acetate; Xylene; N-butyl acetate

UFI: Q3G6-90UU-U00W-1JVK

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration		
CAS:	28182-81-2 931-274-8	Hexamethylene diiso	Hexamethylene diisocyanate, oligomers ⁽¹⁾ Self-classified			
EC: Index: REACH:			Acute Tox. 4: H332; Skin Sens. 1: H317; STOT SE 3: H335 - Warning	35 - <45 %		
CAS:	112-07-2	2-butoxyethyl acetate	e ⁽¹⁾ ATP CLP00			
EC: 203-933-3 Index: 607-038-00-2 REACH: 01-2119475112-47- XXXX		-47- Regulation 1272/2008 Acute Tox. 4: H312+H332 - Warning		10 - <18 %		
CAS: EC:	1330-20-7	Xylene ⁽¹⁾	Self-classified			
EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32- XXXX		Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger			
CAS:	123-86-4	N-butyl acetate ⁽¹⁾	ATP CLP00			
EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29- XXXX		Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	5 - <15 %		
CAS:	128601-23-0	Hydrocarbons, C9, are	omatics ⁽¹⁾ Self-classified			
EC: 918-668-5 Index: Non-applicable REACH: 01-2119455851-35- XXXX		Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger	5 - <10 %		
CAS: 108-65-6		2-methoxy-1-methyle	ethyl acetate ⁽¹⁾ Self-classified			
EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29- XXXX	607-195-00-7 01-2119475791-29-	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	2,5 - <10 %		

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878 ⁽²⁾ Substance with a Union workplace exposure limit

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation

0RS311P-2.5L

Date of compilation: 06/05/2022

Profir

Revised: 03/03/2023

Version: 2 (Replaced 1)

	Identification		Chemical name/Classification			
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35- XXXX		Ethylbenzene ⁽¹⁾	ATP ATP06			
		Regulation 1272/2008	Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger			
CAS:	141-78-6	Ethyl acetate ⁽²⁾	ATP CLP00			
Index: 60 REACH: 01	205-500-4 :: 607-022-00-5 H: 01-2119475103-46- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	<1 %		

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2).


Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation

PROFIRS

0RS311P-2.5L

Date of compilation: 06/05/2022 Revised: 03/03/2023

/03/2023 Vei

Version: 2 (Replaced 1)

SECTION 5: FIREFIGHTING MEASURES (continued)

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene


Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage



Profir

0RS311P-2.5L

Date of compilation: 06/05/2022 Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 7: HANDLING AND STORAGE (continued)

5 °C Minimum Temp.: 25 °C Maximum Temp.: 9 Months Maximum time:

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

Specific end use(s): 7.3

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 **Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

	Identification	Occup	Occupational exposure limits		
2-butoxyethyl ace	etate	IOELV (8h)	20 ppm	133 mg/m ³	
CAS: 112-07-2	EC: 203-933-3	IOELV (STEL)	50 ppm	333 mg/m ³	
Xylene		IOELV (8h)	50 ppm	221 mg/m ³	
CAS: 1330-20-7	EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m ³	
N-butyl acetate		IOELV (8h)	50 ppm	241 mg/m ³	
CAS: 123-86-4	EC: 204-658-1	IOELV (STEL)	150 ppm	723 mg/m ³	
Ethylbenzene		IOELV (8h)	100 ppm	442 mg/m ³	
CAS: 100-41-4	EC: 202-849-4	IOELV (STEL)	200 ppm	884 mg/m ³	
2-methoxy-1-met	hylethyl acetate	IOELV (8h)	50 ppm	275 mg/m ³	
CAS: 108-65-6	EC: 203-603-9	IOELV (STEL)	100 ppm	550 mg/m ³	
Ethyl acetate		IOELV (8h)	200 ppm	734 mg/m ³	
CAS: 141-78-6	EC: 205-500-4	IOELV (STEL)	400 ppm	1468 mg/m ³	

DNEL (Workers):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Hexamethylene diisocyanate, oligomers	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 28182-81-2	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 931-274-8	Inhalation	Non-applicable	1 mg/m ³	Non-applicable	0,5 mg/m ³
2-butoxyethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 112-07-2	Dermal	120 mg/kg	Non-applicable	169 mg/kg	Non-applicable
EC: 203-933-3	Inhalation	Non-applicable	333 mg/m ³	133 mg/m ³	Non-applicable
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
N-butyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-86-4	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
EC: 204-658-1	Inhalation	600 mg/m ³	600 mg/m ³	300 mg/m ³	300 mg/m ³
Hydrocarbons, C9, aromatics	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 128601-23-0	Dermal	Non-applicable	Non-applicable	25 mg/kg	Non-applicable
EC: 918-668-5	Inhalation	Non-applicable	Non-applicable	150 mg/m ³	Non-applicable
Ethylbenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	550 mg/m ³	275 mg/m ³	Non-applicable

PROFIRS color

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS311P-2.5L

Date of compilation: 06/05/2022

Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)							
]			Short exposure Long e			kposure	
	Identification		Systemic	Local	Systemic	Local	
	Ethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
	CAS: 141-78-6	Dermal	Non-applicable	Non-applicable	63 mg/kg	Non-applicable	
	EC: 205-500-4	Inhalation	1468 mg/m ³	1468 mg/m ³	734 mg/m ³	734 mg/m ³	

DNEL (General population):

			exposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
2-butoxyethyl acetate	Oral	36 mg/kg	Non-applicable	8,6 mg/kg	Non-applicable
CAS: 112-07-2	Dermal	72 mg/kg	Non-applicable	102 mg/kg	Non-applicable
EC: 203-933-3	Inhalation	Non-applicable	200 mg/m ³	80 mg/m ³	Non-applicable
Xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³
N-butyl acetate	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable
CAS: 123-86-4	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable
EC: 204-658-1	Inhalation	300 mg/m ³	300 mg/m ³	35,7 mg/m ³	35,7 mg/m ³
Hydrocarbons, C9, aromatics	Oral	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
CAS: 128601-23-0	Dermal	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
EC: 918-668-5	Inhalation	Non-applicable	Non-applicable	32 mg/m ³	Non-applicable
Ethylbenzene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m ³	33 mg/m ³
Ethyl acetate	Oral	Non-applicable	Non-applicable	4,5 mg/kg	Non-applicable
CAS: 141-78-6	Dermal	Non-applicable	Non-applicable	37 mg/kg	Non-applicable
EC: 205-500-4	Inhalation	734 mg/m ³	734 mg/m ³	367 mg/m ³	367 mg/m ³

PNEC:

Identification				
Hexamethylene diisocyanate, oligomers	STP	88 mg/L	Fresh water	0,127 mg/L
CAS: 28182-81-2	Soil	53183 mg/kg	Marine water	0,013 mg/L
EC: 931-274-8	Intermittent	1,27 mg/L	Sediment (Fresh water)	266701 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	26670 mg/kg
2-butoxyethyl acetate	STP	90 mg/L	Fresh water	0,304 mg/L
CAS: 112-07-2	Soil	0,415 mg/kg	Marine water	0,03 mg/L
EC: 203-933-3	Intermittent	0,56 mg/L	Sediment (Fresh water)	2,03 mg/kg
	Oral	0,06 g/kg	Sediment (Marine water)	0,203 mg/kg
Xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
N-butyl acetate	STP	35,6 mg/L	Fresh water	0,18 mg/L
CAS: 123-86-4	Soil	0,09 mg/kg	Marine water	0,018 mg/L
EC: 204-658-1	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Profir

0RS311P-2.5L

Date of compilation: 06/05/2022

SE(

Revised: 03/03/2023

Version: 2 (Replaced 1)

compliation.	00/03/2022	KEVISE(

TON 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)					
Identification					
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0,635 mg/L	
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water	0,064 mg/L	
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg	
Ethyl acetate	STP	650 mg/L	Fresh water	0,24 mg/L	
CAS: 141-78-6	Soil	0,148 mg/kg	Marine water	0,024 mg/L	
EC: 205-500-4	Intermittent	1,65 mg/L	Sediment (Fresh water)	1,15 mg/kg	
	Oral	0,2 g/kg	Sediment (Marine water)	0,115 mg/kg	

8.2 **Exposure controls:**

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Antistatic and fireproof protective clothing		EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
Mandatory foot protection	Safety footwear with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011	Replace boots at any sign of deterioration.

0RS311P-2.5L

СТ	TON 8: EXPOSURE CONTROL	S/PERSONAL PRO	TECTION (co	ntinued)	
	Emergency measure	Standards		Emergency measure	Standards
		Standards			Stanuarus
		ANSI Z358-		*	DIN 12 899
	Emergency shower	ISO 3864-1:2011, ISO	3864-4:2011	Eyewash stations	ISO 3864-1:2011, ISO 3864-4:2011
	Environmental exposure cont	role		Lycwash stations	
	-		protection of the	environment it is recomm	nended to avoid environmental spilla
	of both the product and its conta				
ECT	TION 9: PHYSICAL AND CHEM	ICAL PROPERTIES	S		
1	Information on basic physica	l and chemical pro	perties:		
	Appearance:				
	Physical state at 20 °C:		Liquid		
	Appearance:		Fluid		
	Colour:		Colourless		
	Odour:		Characterist	ic	
	Odour threshold:		Non-applica	ble *	
	Volatility:				
	Boiling point at atmospheric pres	sure:	149 °C		
	Vapour pressure at 20 °C:		717 Pa		
	Vapour pressure at 50 °C:		3663,62 Pa	(3,66 kPa)	
	Evaporation rate at 20 °C:		Non-applica	ble *	
	Product description:				
	Density at 20 °C:		980 - 1000	kg/m³	
	Relative density at 20 °C:		0,98 - 1		
	Dynamic viscosity at 20 °C:		Non-applica	ble *	
	Kinematic viscosity at 20 °C:		Non-applica	ble *	
	Kinematic viscosity at 40 °C:		<20,5 mm²,	/s	
	Concentration:		Non-applica	ble *	
	pH:		Non-applica	ble *	
	Vapour density at 20 °C:		Non-applica	ble *	
	Partition coefficient n-octanol/wa	ter 20 ºC:	Non-applica	ble *	
	Solubility in water at 20 °C:		Non-applica	ble *	
	Solubility properties:		Non-applica	ble *	
	Decomposition temperature:		Non-applica	ble *	
	Melting point/freezing point:		Non-applica	ble *	
	Flammability:				
	Flash Point:		37 °C		
	Flammability (solid, gas):		Non-applica	ble *	
	Autoignition temperature:		300 °C		
	Lower flammability limit:		Not available	e	
	Upper flammability limit:		Not available	e	
	Particle characteristics:				



0RS311P-2.5L

Date of	compilation: 06/05/2022 Revised: 03/03/2023	Version: 2 (Replaced 1)
SECT	TION 9: PHYSICAL AND CHEMICAL PROPERTIES	(continued)
9.2	Other information:	
	Information with regard to physical hazard clas	ses:
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Corrosive to metals:	Non-applicable *
	Heat of combustion:	Non-applicable *
	Aerosols-total percentage (by mass) of flammable components:	Non-applicable *
	Other safety characteristics:	
	Surface tension at 20 °C:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product, not providing infor	nation property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation



0RS311P-2.5L

Date of compilation: 06/05/2022 Revised: 03/03/2023 Version: 2 (Replaced 1)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
 - IARC: Hydrocarbons, C9, aromatics (3); Xylene (3); Ethylbenzene (2B)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity	Genus
N-butyl acetate	LD50 oral 12789 mg/kg	Rat
CAS: 123-86-4	LD50 dermal 14112 mg/kg	Rabbit
EC: 204-658-1	LC50 inhalation 23,4 mg/L (4 h)	Rat
2-methoxy-1-methylethyl acetate	LD50 oral 8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal >5000 mg/kg	Rat
EC: 203-603-9	LC50 inhalation 30 mg/L (4 h)	Rat
2-butoxyethyl acetate	LD50 oral 2100 mg/kg	Rat
CAS: 112-07-2	LD50 dermal 1480 mg/kg	Rabbit
EC: 203-933-3	LC50 inhalation 11 mg/L (4 h)	Rat
Xylene	LD50 oral 2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal 1100 mg/kg	Rat
EC: 215-535-7	LC50 inhalation 11 mg/L (ATEi)	
Ethylbenzene	LD50 oral 3500 mg/kg	Rat
CAS: 100-41-4	LD50 dermal 15354 mg/kg	Rabbit
EC: 202-849-4	LC50 inhalation 17,2 mg/L (4 h)	Rat
Hexamethylene diisocyanate, oligomers	LD50 oral 5100 mg/kg	Rat
CAS: 28182-81-2	LD50 dermal Non-applicable	
EC: 931-274-8	LC50 inhalation 11 mg/L (ATEi)	

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



0RS311P-2.5L

Date of compilation: 06/05/2022

Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification		Acute toxicity	Genus
Ethyl acetate	LD50 oral	4100 mg/kg	Rat
CAS: 141-78-6	LD50 dermal	20000 mg/kg	Rabbit
EC: 205-500-4	LC50 inhalation	Non-applicable	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
Hexamethylene diisocyanate, oligomers	LC50	Non-applicable		
CAS: 28182-81-2	EC50	Non-applicable		
EC: 931-274-8	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae
2-butoxyethyl acetate	LC50	80 mg/L (48 h)	Leuciscus idus	Fish
CAS: 112-07-2	EC50	37 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-933-3	EC50	500 mg/L (72 h)	Scenedesmus subspicatus	Algae
Xylene	LC50	>10 - 100 mg/L (96 h)		Fish
CAS: 1330-20-7	EC50	>10 - 100 mg/L (48 h)		Crustacean
EC: 215-535-7	EC50	>10 - 100 mg/L (72 h)		Algae
N-butyl acetate	LC50	Non-applicable		
CAS: 123-86-4	EC50	Non-applicable		
EC: 204-658-1	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Hydrocarbons, C9, aromatics	LC50	>1 - 10 mg/L (96 h)		Fish
CAS: 128601-23-0	EC50	>1 - 10 mg/L (48 h)		Crustacean
EC: 918-668-5	EC50	>1 - 10 mg/L (72 h)		Algae
Ethylbenzene	LC50	42,3 mg/L (96 h)	Pimephales promelas	Fish
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
EC: 203-603-9	EC50	Non-applicable		
Ethyl acetate	LC50	230 mg/L (96 h)	Pimephales promelas	Fish
CAS: 141-78-6	EC50	717 mg/L (48 h)	Daphnia magna	Crustacean
EC: 205-500-4	EC50	3300 mg/L (48 h)	Scenedesmus subspicatus	Algae

Chronic toxicity:

Identification		Concentration	Species	Genus
Xylene	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
CAS: 1330-20-7 EC: 215-535-7	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
N-butyl acetate	NOEC	Non-applicable		
CAS: 123-86-4 EC: 204-658-1	NOEC	23,2 mg/L	Daphnia magna	Crustacean
Ethylbenzene	NOEC	Non-applicable		
CAS: 100-41-4 EC: 202-849-4	NOEC	0,96 mg/L	Ceriodaphnia dubia	Crustacean
2-methoxy-1-methylethyl acetate	NOEC	47,5 mg/L	Oryzias latipes	Fish
CAS: 108-65-6 EC: 203-603-9	NOEC	100 mg/L	Daphnia magna	Crustacean

- CONTINUED ON NEXT PAGE -

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

PROFIRS color

0RS311P-2.5L

Date of compilation: 06/05/2022

Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification		Concentration	Species	Genus
Ethyl acetate	NOEC	9,65 mg/L	Pimephales promelas	Fish
CAS: 141-78-6 EC: 205-500-4	NOEC	2,4 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	De	egradability	Biod	egradability
2-butoxyethyl acetate	BOD5	Non-applicable	Concentration	30 mg/L
CAS: 112-07-2	COD	Non-applicable	Period	28 days
EC: 203-933-3	BOD5/COD	Non-applicable	% Biodegradable	77,3 %
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %
N-butyl acetate	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 123-86-4	COD	Non-applicable	Period	5 days
EC: 204-658-1	BOD5/COD	Non-applicable	% Biodegradable	84 %
Ethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-41-4	COD	Non-applicable	Period	14 days
EC: 202-849-4	BOD5/COD	Non-applicable	% Biodegradable	90 %
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L
CAS: 108-65-6	COD	Non-applicable	Period	8 days
EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
Ethyl acetate	BOD5	1,36 g O2/g	Concentration	100 mg/L
CAS: 141-78-6	COD	1,69 g O2/g	Period	14 days
EC: 205-500-4	BOD5/COD	0,8	% Biodegradable	83 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification		Bioaccumulation potential		
2-butoxyethyl acetate		BCF	3	
CAS: 112-07-2		Pow Log	1.51	
EC: 203-933-3		Potential	Low	
Xylene		BCF	9	
CAS: 1330-20-7		Pow Log	2.77	
EC: 215-535-7		Potential	Low	
N-butyl acetate		BCF	4	
CAS: 123-86-4		Pow Log	1.78	
EC: 204-658-1		Potential	Low	
Ethylbenzene		BCF	1	
CAS: 100-41-4		Pow Log	3.15	
C: 202-849-4		Potential	Low	
2-methoxy-1-methylethyl acetate		BCF	1	
CAS: 108-65-6		Pow Log	0.43	
EC: 203-603-9		Potential	Low	
Ethyl acetate		BCF	30	
CAS: 141-78-6		Pow Log	0.73	
EC: 205-500-4		Potential	Moderate	

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
2-butoxyethyl acetate	Кос	Non-applicable	Henry	5,532E-1 Pa·m³/mol
CAS: 112-07-2	Conclusion	Non-applicable	Dry soil	No
EC: 203-933-3	Surface tension	Non-applicable	Moist soil	Yes



legislation

0RS311P-2.5L

Date of compilation: 06/05/2022

Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absor	Absorption/desorption		Volatility	
Xylene	Кос	202	Henry	524,86 Pa·m ³ /mol	
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes	
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes	
N-butyl acetate	Кос	Non-applicable	Henry	Non-applicable	
CAS: 123-86-4	Conclusion	Non-applicable	Dry soil	Non-applicable	
EC: 204-658-1	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable	
Ethylbenzene	Кос	520	Henry	798,44 Pa·m³/mol	
CAS: 100-41-4	Conclusion	Moderate	Dry soil	Yes	
EC: 202-849-4	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes	
Ethyl acetate	Кос	59	Henry	13,58 Pa·m³/mol	
CAS: 141-78-6	Conclusion	Very High	Dry soil	Yes	
EC: 205-500-4	Surface tension	2,324E-2 N/m (25 °C)	Moist soil	Yes	

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous	

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable, HP6 Acute Toxicity, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

PROFIRS

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS311P-2.5L

Date of compilation: 06/05/2022	Revised: 03/03/2023	Version: 2 (Replaced 1)
SECTION 14: TRANSPORT I	NFORMATION (continued)	
14.2 14.3 14.4 14.5 14.6	UN number or ID number: UN proper shipping name: Transport hazard class(es): Labels: Packing group: Environmental hazards: Special precautions for user Special regulations: Tunnel restriction code: Physico-Chemical properties: Limited quantities:	UN1263 PAINT RELATED MATERIAL 3 3 III No 163, 367, 650 D/E see section 9 5 L
14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable
Transport of dangerou	us goods by sea:	
With regard to IMDG 40-	-20:	
14.1	UN number or ID number:	UN1263
14.2	UN proper shipping name:	PAINT RELATED MATERIAL
14.3	Transport hazard class(es):	3
	Labels:	3
14.4	Packing group:	III
14.5	Marine pollutant:	No
V 14.6	Special precautions for user	
	Special regulations:	163, 223, 955, 367
	EmS Codes:	F-E, S-E
	Physico-Chemical properties:	see section 9
	Limited quantities:	5 L
	Segregation group:	Non-applicable
14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable
Transport of dangerou	us goods by air:	
With regard to IATA/ICA	O 2022:	
14.1	UN number or ID number:	UN1263
14.2	UN proper shipping name:	PAINT RELATED MATERIAL
	Transport hazard class(es):	3
	Labels:	3
14.4	Packing group:	III
14.5	Environmental hazards:	No
14.6	Special precautions for user	
	Physico-Chemical properties:	see section 9
14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable



0RS311P-2.5L

Date of compilation: 06/05/2022 Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 15: REGULATORY INFORMATION (continued)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements				
P5c	FLAMMABLE LIQUIDS	5000	50000				
Limitations):	Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):						

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

PROFIRS

0RS311P-2.5L

Date of compilation: 06/05/2022 Revised: 03/03/2023 Version: 2 (Replaced 1) SECTION 15: REGULATORY INFORMATION (continued) Shall not be used in: and ashtrays, -tricks and jokes, -games for one or more participants, or any article intended to be used as such, even with ornamental aspects. Contains more than 0.1 % of Hexamethylene diisocyanate, oligomers by weight. 1. Shall not be used as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 August 2023, unless: (a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the employer or selfemployed ensures that industrial or professional user(s) have successfully completed training on the safe use of diisocyanates prior to the use of the substance(s) or mixture(s). 2. Shall not be placed on the market as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 February 2022, unless: (a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the supplier ensures that the recipient of the substance(s) or mixture(s) is provided with information on the requirements referred to in point (b) of paragraph 1 and the following statement is placed on the packaging, in a manner that is visibly distinct from the rest of the label information: "As from 24 August 2023 adequate training is required before industrial or professional use". 3. For the purpose of this entry "industrial and professional user(s)" means any worker or self-employed worker handling diisocyanates on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) or supervising these tasks. 4. The training referred to in point (b) of paragraph 1 shall include the instructions for the control of dermal and inhalation exposure to diisocyanates at the workplace without prejudice to any national occupational exposure limit value or other appropriate risk management measures at national level. Such training shall be conducted by an expert on occupational safety and health with competence acquired by relevant vocational training. That training shall cover as a minimum: (a) the training elements in point (a) of paragraph 5 for all industrial and professional use(s). (b) the training elements in points (a) and (b) of paragraph 5 for the following uses: - handling open mixtures at ambient temperature (including foam tunnels) - spraying in a ventilated booth - application by roller application by brush
 application by dipping and pouring - mechanical post treatment (e.g. cutting) of not fully cured articles which are not warm anymore - cleaning and waste - any other uses with similar exposure through the dermal and/or inhalation route (c) the training elements in points (a), (b) and (c) of paragraph 5 for the following uses: handling incompletely cured articles (e.g. freshly cured, still warm) - foundry applications - maintenance and repair that needs access to equipment open handling of warm or hot formulations (> 45 °C) spraying in open air, with limited or only natural ventilation (includes large industry working halls) and spraying with high energy (e.g. foams, elastomers) - and any other uses with similar exposure through the dermal and/or inhalation route. 5. Training elements: (a) general training, including on-line training, on: chemistry of diisocyanates - toxicity hazards (including acute toxicity) - exposure to diisocyanates occupational exposure limit values - how sensitisation can develop - odour as indication of hazard - importance of volatility for risk - viscosity, temperature, and molecular weight of diisocyanates personal hygiene personal protective equipment needed, including practical instructions for its correct use and its limitations
 risk of dermal contact and inhalation exposure - risk in relation to application process used - skin and inhalation protection scheme - ventilation - cleaning, leakages, maintenance - discarding empty packaging - protection of bystanders - identification of critical handling stages specific national code systems (if applicable)

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



0RS311P-2.5L

Date of compilation: 06/05/2022 Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 15: REGULATORY INFORMATION (continued)

- behaviour-based safety
- certification or documented proof that training has been successfully completed
- (b) intermediate level training, including on-line training, on:
- additional behaviour-based aspects
 maintenance
- management of change
- evaluation of existing safety instructions
- risk in relation to application process used
- certification or documented proof that training has been successfully completed
- (c) advanced training, including on-line training, on:
- any additional certification needed for the specific uses covered
- spraying outside a spraying booth
- open handling of hot or warm formulations (> 45 °C)
- certification or documented proof that training has been successfully completed

6. The training shall comply with the provisions set by the Member State in which the industrial or professional user(s) operate. Member States may implement or continue to apply their own national requirements for the use of the substance(s) or mixture (s), as long as the minimum requirements set out in paragraphs 4 and 5 are met.

7. The supplier referred to in point (b) of paragraph 2 shall ensure that the recipient is provided with training material and courses pursuant to paragraphs 4 and 5 in the official language(s) of the Member State(s) where the substance(s) or mixture(s) are supplied. The training shall take into consideration the specificity of the products supplied, including composition, packaging, and design.

8. The employer or self-employed shall document the successful completion of the training referred to in paragraphs 4 and 5. The training shall be renewed at least every five years.

9. Member States shall include in their reports pursuant to Article 117(1) the following information:

(a) any established training requirements and other risk management measures related to the industrial and professional uses of diisocyanates foreseen in national law

(b) the number of cases of reported and recognised occupational asthma and occupational respiratory and dermal diseases in relation to diisocyanates

(c) national exposure limits for diisocyanates, if there are any

(d) information about enforcement activities related to this restriction.

10. This restriction shall apply without prejudice to other Union legislation on the protection of safety and health of workers at the workplace.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.: Non-applicable

Texts of the legislative phrases mentioned in section 2:

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation



0RS311P-2.5L

Date of compilation: 06/05/2022 Revised: 03/03/2023 Version: 2 (Replaced 1) SECTION 16: OTHER INFORMATION (continued) H317: May cause an allergic skin reaction. H335: May cause respiratory irritation. H336: May cause drowsiness or dizziness. H412: Harmful to aquatic life with long lasting effects. H315: Causes skin irritation. H373: May cause damage to organs through prolonged or repeated exposure (Oral). H332: Harmful if inhaled. H304: May be fatal if swallowed and enters airways. H226: Flammable liquid and vapour. H319: Causes serious eye irritation. Texts of the legislative phrases mentioned in section 3: The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 CLP Regulation (EC) No 1272/2008: Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled. Acute Tox. 4: H332 - Harmful if inhaled. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Lig. 2: H225 - Highly flammable liquid and vapour. Flam. Lig. 3: H226 - Flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. **Classification procedure:** Skin Sens. 1: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method Aquatic Chronic 3: Calculation method Skin Irrit. 2: Calculation method STOT RE 2: Calculation method Acute Tox. 4: Calculation method Asp. Tox. 1: Calculation method Flam. Liq. 3: Calculation method (2.6.4.3) Eye Irrit. 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu Abbreviations and acronyms: ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

0RS311P-2.5L

Date of compilation: 06/05/2022

Revised: 03/03/2023

Version: 2 (Replaced 1)

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

