

legislation

0RS390-0.5L

ate of	compilation: 14/10/2021	Revised: 03/03/2023	Version: 2 (Replaced 1)
SEC	TION 1: IDENTIFICATION	NOF THE SUBSTANCE/M	IXTURE AND OF THE COMPANY/UNDERTAKING
1.1	Product identifier:	0RS390-0.5L	
	Other means of identific	ation:	
	UFI:	A1E6-509A-H0	01-5CW1
1.2	Relevant identified uses	of the substance or mixt	ure and uses advised against:
	Relevant uses: Anticorrosion	n primer. For professional us	ers only.
	Uses advised against: All us	ses not specified in this section	on or in section 7.3
1.3	Details of the supplier of	f the safety data sheet:	
	Inter Cars S.A. ul. Powsińska 64 02-903 Warszawa - Polska		
1.4	kontakt@intercars.com www.intercars.com Emergency telephone nu	umber:	
	kontakt@intercars.com www.intercars.com		
	kontakt@intercars.com www.intercars.com Emergency telephone nu	TFICATION **	
SEC	kontakt@intercars.com www.intercars.com Emergency telephone nu TION 2: HAZARDS IDENT	IFICATION ** stance or mixture:	
SEC	kontakt@intercars.com www.intercars.com Emergency telephone nu TION 2: HAZARDS IDENT Classification of the sub CLP Regulation (EC) No	TFICATION ** stance or mixture: 1272/2008:	ordance with CLP Regulation (EC) No 1272/2008.

2.2 Label elements:

PROFIRS

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure (Oral).
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

** Changes with regards to the previous version



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation

0RS390-0.5L

Date of compilation: 14/10/2021

Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 2: HAZARDS IDENTIFICATION ** (continued)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Substances that contribute to the classification

Toluene; Xylene; Ethylbenzene; Benzophenone

UFI: A1E6-509A-H001-5CW1

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

Endocrine-disrupting properties: The product fails to meet the criteria.

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification				
CAS:			ATP CLP00				
REACH:	203-625-9 601-021-00-3 01-2119471310-51- XXXX	Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	40 - <50 %			
CAS:	1330-20-7	Xylene ⁽¹⁾	Self-classified				
Index: REACH:	215-535-7 601-022-00-9 01-2119488216-32- XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	30 - <38 %			
CAS: 100-41-4		Ethylbenzene ⁽¹⁾	ATP ATP06				
			Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger				
CAS:	119-61-9	Benzophenone ⁽¹⁾	Self-classified				
REACH:	204-337-6 Non-applicable 01-2119488052-40- XXXX	Regulation 1272/2008	Aquatic Chronic 3: H412; STOT RE 2: H373 - Warning	1 - <2,5 %			
CAS: 64742-82-1		naphtha (petroleum)), hydrodesulphurized heavy , < 0.1 % EC 200-753-7(1) ATP ATP05				
	265-185-4 649-330-00-2 01-2119490979-12- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger	1 - <2,5 %			

(1) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation

0RS390-0.5L

Date of compilation: 14/10/2021 Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 4: FIRST AID MEASURES (continued)

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground. **For emergency responders:**

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation

0RS390-0.5L

Date of compilation: 14/10/2021

Profir

Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

	-
Minimum Temp.:	5 °C
Maximum Temp.:	25 °C
Maximum time:	24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation

PROFIRS

0RS390-0.5L

Date of compilation: 14/10/2021

Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

	Identification	Occupational exposure limits		
Toluene		IOELV (8h)	50 ppm	192 mg/m ³
CAS: 108-88-3	EC: 203-625-9	IOELV (STEL)	100 ppm	384 mg/m ³
Xylene		IOELV (8h)	50 ppm	221 mg/m ³
CAS: 1330-20-7	EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m ³
Ethylbenzene		IOELV (8h)	100 ppm	442 mg/m ³
CAS: 100-41-4	EC: 202-849-4	IOELV (STEL)	200 ppm	884 mg/m ³

DNEL (Workers):


		Short e	xposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Toluene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	384 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	384 mg/m ³	384 mg/m ³	192 mg/m ³	192 mg/m ³
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
Ethylbenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
Benzophenone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 119-61-9	Dermal	Non-applicable	Non-applicable	0,1 mg/kg	Non-applicable
EC: 204-337-6	Inhalation	Non-applicable	Non-applicable	0,7 mg/m ³	Non-applicable
naphtha (petroleum), hydrodesulphurized heavy , < 0.1 $\%$ EC 200-753-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-82-1	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 265-185-4	Inhalation	1286,4 mg/m ³	1066,67 mg/m ³	Non-applicable	837,5 mg/m ³

DNEL (General population):

		Short e	xposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
Toluene	Oral	Non-applicable	Non-applicable	8,13 mg/kg	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	226 mg/m ³	226 mg/m ³	56,5 mg/m³	56,5 mg/m ³
Xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³
Ethylbenzene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable
Benzophenone	Oral	Non-applicable	Non-applicable	0,05 mg/kg	Non-applicable
CAS: 119-61-9	Dermal	Non-applicable	Non-applicable	0,05 mg/kg	Non-applicable
EC: 204-337-6	Inhalation	Non-applicable	Non-applicable	0,17 mg/m ³	Non-applicable
naphtha (petroleum), hydrodesulphurized heavy , < 0.1 % EC 200-753-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-82-1	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 265-185-4	Inhalation	1152 mg/m ³	640 mg/m ³	Non-applicable	178,57 mg/m ³

PNEC:

Identification				
Toluene	STP	13,61 mg/L	Fresh water	0,68 mg/L
CAS: 108-88-3	Soil	2,89 mg/kg	Marine water	0,68 mg/L
EC: 203-625-9	Intermittent	0,68 mg/L	Sediment (Fresh water)	16,39 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16,39 mg/kg



legislation

Profir

0RS390-0.5L

Date of compilation: 14/10/2021

Version: 2 (Replaced 1)

Revised: 03/03/2023

DDOTECTION	(-

Identification				
(ylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg
Benzophenone	STP	3,16 mg/L	Fresh water	0,02 mg/L
CAS: 119-61-9	Soil	0,31 mg/kg	Marine water	0,002 mg/L
EC: 204-337-6	Intermittent	0,035 mg/L	Sediment (Fresh water)	1,1 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,11 mg/kg

8.2 **Exposure controls:**

A.- Individual protection measures, such as personal protective equipment

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	CAT II	EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS390-0.5L

21 Revised: 03/03	/2023 V	/ersion: 2 (Replaced 1)		
CONTROLS/PERSON	AL PROTECTI	ON (continued)		
PPE	Labelling	CEN Standard		Remarks
Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CAT III	EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Re	eplace boots at any sign of deterioration.
				Chandanda
asure St	andards	Emergency measure	ure	Standards
		11 Eyewash station	IS	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
•	CONTROLS/PERSONA PPE Safety footwear for protection against chemical risk, with antistatic and heat resistant properties ency measures asure Sta	PPE Labelling Safety footwear for protection against chemical risk, with antistatic and heat resistant properties CAT III ency measures Standards asure Standards ANSI Z358-1 ANSI Z358-1	PPE Labelling CEN Standard Safety footwear for protection against chemical risk, with antistatic and heat resistant properties EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019 ency measures asure Standards Ency measures Standards Emergency measures	PPE Labelling CEN Standard Safety footwear for protection against chemical resistant properties EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019 Re ency measures asure Standards Emergency measure ANSI Z358-1 Image: Center of the standard stan

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1	Information on basic physical and chemical	properties:
	Appearance:	
	Physical state at 20 °C:	Liquid
	Appearance:	Fluid
	Colour:	Amber
	Odour:	Characteristic
	Odour threshold:	Non-applicable *
	Volatility:	
	Boiling point at atmospheric pressure:	123 °C
	Vapour pressure at 20 °C:	Non-applicable *
	Vapour pressure at 50 °C:	Non-applicable *
	Evaporation rate at 20 °C:	Non-applicable *
	Product description:	
	Density at 20 °C:	860 - 880 kg/m³
	Relative density at 20 °C:	0,86 - 0,88
	Dynamic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 40 °C:	<20,5 mm²/s
	Concentration:	Non-applicable *
	pH:	Non-applicable *
	Vapour density at 20 °C:	Non-applicable *
	Partition coefficient n-octanol/water 20 °C:	Non-applicable *
	Solubility in water at 20 °C:	Non-applicable *
	Solubility properties:	Non-applicable *
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Flammability:	
	Flash Point:	14 °C
	*Not relevant due to the nature of the product, not providing	g information property of its hazards.



Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS390-0.5L

Date of	compilation: 14/10/2021 Re	evised: 03/03/2023	Version: 2 (Replaced 1)	
SECT	TION 9: PHYSICAL AND CHEM	IICAL PROPERTIES	(continued)	
	Flammability (solid, gas):		Non-applicable *	
	Autoignition temperature:		275 °C	
	Lower flammability limit:		Not available	
	Upper flammability limit:		Not available	
	Particle characteristics:			
	Median equivalent diameter:		Non-applicable	
9.2	Other information:			
	Information with regard to p	hysical hazard class	ies:	
	Explosive properties:		Non-applicable *	
	Oxidising properties:		Non-applicable *	
	Corrosive to metals:		Non-applicable *	
	Heat of combustion:		Non-applicable *	
	Aerosols-total percentage (by ma components:	ss) of flammable	Non-applicable *	
	Other safety characteristics:			
	Surface tension at 20 °C:		Non-applicable *	
	Refraction index:		Non-applicable *	
	*Not relevant due to the nature of the p	roduct, not providing inforr	nation property of its hazards.	

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO_2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available


Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure: A- Ingestion (acute effect):

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Profir

0RS390-0.5L



	Identification	A	cute toxicity	Genus
Xylene		LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7		LD50 dermal	1100 mg/kg	Rat
EC: 215-535-7		LC50 inhalation	11 mg/L (ATEi)	
Ethylbenzene		LD50 oral	3500 mg/kg	Rat
CAS: 100-41-4		LD50 dermal	15354 mg/kg	Rabbit
EC: 202-849-4		LC50 inhalation	17,2 mg/L (4 h)	Rat
Toluene		LD50 oral	5580 mg/kg	Rat
CAS: 108-88-3		LD50 dermal	12124 mg/kg	Rat
EC: 203-625-9		LC50 inhalation	28,1 mg/L (4 h)	Rat
Benzophenone		LD50 oral	3350 mg/kg	Rat
CAS: 119-61-9		LD50 dermal	3535 mg/kg	
EC: 204-337-6		LC50 inhalation	Non-applicable	



legislation

0RS390-0.5L

Date of compilation: 14/10/2021

PROFIRE

Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	A	cute toxicity	Genus
naphtha (petroleum), hydrodesulphurized heavy , < 0.1 % EC 200-753-7	LD50 oral	5100 mg/kg	Rat
CAS: 64742-82-1	LD50 dermal	3160 mg/kg	Rabbit
EC: 265-185-4	LC50 inhalation	12 mg/L (6 h)	Rat

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
Toluene	LC50	5,5 mg/L (96 h)	Oncorhynchus kisutch	Fish
CAS: 108-88-3	EC50	3,78 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
EC: 203-625-9	EC50	Non-applicable		
Xylene	LC50	>10 - 100 mg/L (96 h)		Fish
CAS: 1330-20-7	EC50	>10 - 100 mg/L (48 h)		Crustacean
EC: 215-535-7	EC50	>10 - 100 mg/L (72 h)		Algae
Ethylbenzene	LC50	42,3 mg/L (96 h)	Pimephales promelas	Fish
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
Benzophenone	LC50	15,3 mg/L (96 h)	Pimephales promelas	Fish
CAS: 119-61-9	EC50	Non-applicable		
EC: 204-337-6	EC50	Non-applicable		
naphtha (petroleum), hydrodesulphurized heavy , < 0.1 % EC 200-753-7	LC50	Non-applicable		
CAS: 64742-82-1	EC50	4,3 mg/L (96 h)	Crangon crangon	Crustacean
EC: 265-185-4	EC50	Non-applicable		

Chronic toxicity:

Identification	Identification Concentration		Species	Genus
Xylene	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
CAS: 1330-20-7 EC: 215-535-7	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
Ethylbenzene	NOEC	Non-applicable		
CAS: 100-41-4 EC: 202-849-4	NOEC	0,96 mg/L	Ceriodaphnia dubia	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	De	gradability	Biode	Biodegradability		
Toluene	BOD5	2,5 g O2/g	Concentration	100 mg/L		
CAS: 108-88-3	COD	Non-applicable	Period	14 days		
EC: 203-625-9	BOD5/COD	Non-applicable	% Biodegradable	100 %		
Xylene	BOD5	Non-applicable	Concentration	Non-applicable		
CAS: 1330-20-7	COD	Non-applicable	Period	28 days		
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %		
Ethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L		
CAS: 100-41-4	COD	Non-applicable	Period	14 days		
EC: 202-849-4	BOD5/COD	Non-applicable	% Biodegradable	90 %		



0RS390-0.5L


SECT	TON 12: ECOLOGICAL INFORMATI	ON (continued)						
	Identification	Dec	gradability		Bic	odegrada	bility	
	Benzophenone	BOD5	Non-applicable	Conce	entration		100 mg/L	
	CAS: 119-61-9	COD	Non-applicable	Perio			28 days	
	EC: 204-337-6	BOD5/COD	Non-applicable	% Bio	odegradable		75 %	
12.3	Bioaccumulative potential: Substance-specific information:			•				
	Ide	entification			Bioacc	umulatio	n potential	
	Toluene			BC	F	90		
	CAS: 108-88-3			Po	w Log	2.73		
	EC: 203-625-9	Pot	tential	Mode	rate			
	Xylene	9						
	CAS: 1330-20-7			Po	w Log	2.77		
	EC: 215-535-7			Pot	tential	Low		
	Ethylbenzene			BC	F	1		
	CAS: 100-41-4				w Log	3.15		
	EC: 202-849-4				tential	Low		
	Benzophenone			BC	F	12		
	CAS: 119-61-9				w Log	3.18		
	EC: 204-337-6				tential	Low		
		naphtha (petroleum), hydrodesulphurized heavy , < 0.1 % EC 200-753-7 BCF 645						
	CAS: 64742-82-1	,, , , , , , , , , , , , , , , , , , , ,			w Log	4		
	EC: 265-185-4			Potential High				
12.4	Mobility in soil:							
	Identification	Abso	Absorption/desorption			Vola	tility	
	Toluene	Кос	178		Henry		672,8 Pa·m³/mol	
	CAS: 108-88-3	Conclusion	Moderate		Dry soil		Yes	
	EC: 203-625-9	Surface tension	2,793E-2 N/m(25 ºC)	Moist soil		Yes	
	Xylene	Кос	202		Henry		524,86 Pa·m ³ /mol	
	CAS: 1330-20-7	Conclusion	Moderate		Dry soil		Yes	
	EC: 215-535-7	Surface tension	Non-applicable		Moist soil		Yes	
	Ethylbenzene	Кос	520		Henry		798,44 Pa·m ³ /mol	
	CAS: 100-41-4	Conclusion	Moderate		Dry soil		Yes	
	EC: 202-849-4	Surface tension	2,859E-2 N/m (2	25 ºC)	Moist soil		Yes	
	Benzophenone	Кос	517		Henry		1,97E-1 Pa·m ³ /mol	
	CAS: 119-61-9	Conclusion	Low		Dry soil		Yes	
	EC: 204-337-6	Surface tension	1,765E-2 N/m (2 °C)	295,53	Moist soil		Yes	
L 2.5	Results of PBT and vPvB assessme	nt:	3					
	Product fails to meet PBT/vPvB criteria							
L2.6	Endocrine disrupting properties:							
	Endocrine-disrupting properties: The pr	oduct fails to meet the c	riteria.					
L2.7	Other adverse effects:							

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

PROFI RS

Code	Description	Waste class (Regulation (EU) No 1357/2014)	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances Dangerous		
Type of waste (Regulation (EU) No 1357/2014):			



legislation

0RS390-0.5L

Date of compilation: 14/10/2021

PROFIRE

Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable, HP6 Acute Toxicity, HP10 Toxic for reproduction, HP4 Irritant - skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

	14.1	UN number or ID number:	UN1263
	14.2	UN proper shipping name:	PAINT
JHL .		Transport hazard class(es):	3
$\langle \underline{\mathbf{u}} \rangle$		Labels:	3
	14.4	Packing group:	II
3	14.5	Environmental hazards:	No
•	14.6	Special precautions for user	
		Special regulations:	163, 367, 650
		Tunnel restriction code:	D/E
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable
Transport of da	ngero	us goods by sea:	
With regard to IM	1DG 40	-20:	
	14.1	UN number or ID number:	UN1263
	14.2	UN proper shipping name:	PAINT
	14.3	Transport hazard class(es):	3
		Labels:	3
$\langle - \rangle$		Packing group:	II
3	14.5	Marine pollutant:	No
	14.6	Special precautions for user	
		Special regulations:	367, 163
		EmS Codes:	F-E, S-E
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
		Segregation group:	Non-applicable
	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable
Transport of da	ngero	us goods by air:	
With regard to IA	TA/ICA	O 2022:	

Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



0RS390-0.5L

Date of compilation: 14/10/20	21 Revised: 03/03/2023	Version: 2 (Replaced 1)
SECTION 14: TRANSPO	ORT INFORMATION (continued)	
	 14.1 UN number or ID number: 14.2 UN proper shipping name: 14.3 Transport hazard class(es): Labels: 14.4 Packing group: 14.5 Environmental hazards: 14.6 Special precautions for user 	3 II No
:	Physico-Chemical properties: 14.7 Maritime transport in bulk according to IMO instruments:	see section 9 Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Contains more than 0.1 % of Toluene by weight. Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

** Changes with regards to the previous version

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS390-0.5L

SECTION 16: OTHER INFORMATION ** (continued) COMMISSION REGULATION (EU) 2020/878 CP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):	Date of compilation: 14/10/2021	Revised: 03/03/2023	Version: 2 (Replaced 1)
CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16): 'Hazard statements' Texts of the legislative phrases mentioned in section 2: H315: Causes skin irritation. H336: May cause drowsiness or dizziness. H412: Harmful to aquatic life with long lasting effects. H337: May cause damage to organs through prolonged or repeated exposure (Oral). H337: May cause damage to organs through prolonged or repeated exposure (Oral). H337: May cause damage to organs through prolonged or repeated exposure (Oral). H337: May cause damage to organs through prolonged or repeated exposure. H361d: Suspected of damaging the unborn child. H304: May be fatal if swallowed and enters airways. H225: Highly flammable liquid and vapour. H336: Causes serious eye irritation. Texts of the legislative phrases mentioned in section 3: Texts of the legislative phrases mentioned in section 3: CLP Regulation (EC) No 1272/2008: Acute Tox. 4: H312-H332 - Harmful in contact with skin or if inhaled. Acute Tox. 4: H332 - Harmful in contact with skin or if inhaled. Acute Tox. 4: H332 - Harmful in contact with skin or if inhaled. Acute Tox. 4: H332 - Harmful in contact with skin or if inhaled. Acute Tox. 4: H332 - Harmful in contact with skin or if inhaled. Acute Tox. 4: H332 - Harmful in contact with skin or if inhaled. Acute Tox. 4: H332 - Harmful in aquatic life with long lasting effects. Aquatic Chronic 3: H412 - Harmful in aquate life with long lasting effects. Aquatic Chronic 3: H412 - Harmful in aquate life with long lasting effects. Agus the Agus to the Agus and any population. Flam. Liq. 3: H226 - Hammable liquid and vapour. Flam. Liq. 3: H226 - Hammable liquid and vapour. Flam. Liq. 3: H226 - Hammable liquid and vapour. Flam. Liq. 3: H236 - May cause damage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H337 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H336 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: Alacutation metho	SECTION 16: OTHER INFORM	MATION ** (continued)	
 H315: Causes skin irritation. H336: May cause erroyinatory irritation. H337: May cause drowsiness or dizziness. H412: Harmful to aquatic life with long lasting effects. H337: May cause damage to organs through prolonged or repeated exposure (Oral). H337: May cause damage to organs through prolonged or repeated exposure. H336: Suspected of damaging the unborn child. H304: May be fatal if swallowed and enters airways. H225: Highly flammable liquid and vapour. H319: Causes serious eye irritation. Texts of the legislative phrases mentioned in section 3: The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3: CLP Regulation (EC) No 1272/2008: Acute Tox. 4: H312-H332. Harmful in contact with skin or if inhaled. Acute Tox. 4: H312-H372. Harmful in tinhaled. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Aquatic Chronic 2: H411 - Varxit to aquatic life with long lasting effects. App. Tox. 1: H304 - May be fatal if swallowed and enters airways. Eye Inrt. 2: H315 - Causes serious eye irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Flam. Liq. 2: H235 - May cause edamage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H337 - May cause damage to organs through prolonged or repeated exposure. STOT RE 2: H337 - May cause damage to organs through prolonged or repeated exposure. STOT RE 2: H337 - May cause edamage to organs through prolonged or repeated exposure. STOT RE 2: H337 - May cause edamage to organs through prolonged or repeated exposure. STOT RE 2: H337 - May cause edamage to organs through prolonged or repeated exposure. STOT RE 2: A133 - May cause edamage to organs through prolonged or repeated	CLP Regulation (EC) No 12 · Hazard statements	72/2008 (SECTION 2, SECTI	
 H412: Haimful to aquatic life with long lasting effects. H373: May cause damage to organs through prolonged or repeated exposure (Oral). H374: May be fatal if swallowed and enters airways. H225: Highly flammable liquid and vapour. H319: Causes serious eye irritation. Texts of the legislative phrases mentioned in section 3: The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 CLP Regulation (EC) No 1272/2008: Acute Tox. 4: H312: H312	H315: Causes skin irritation	۱.	
 H373: May cause damage to organs through prolonged or repeated exposure. H361d: Suspected of damaging the unborn child. H304: May be fatal if swallowed and enters airways. H225: Highly flammable liquid and vapour. H319: Causes serious eye irritation. Texts of the legislative phrases mentioned in section 3: The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 CLP Regulation (EC) No 1272/2008: Acute Tox. 4: H312-H332 - Harmful in contact with skin or if inhaled. Acute Tox. 4: H312-H332 - Harmful in contact with skin or if inhaled. Aquatic Chronic 3: H411 - Toxic to aquatic life with long lasting effects. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Eye Inrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 2: H325 - Highly flammable liquid and vapour. Flam. Liq. 3: H326 - Flammable liquid and vapour. Flam. Liq. 3: H326 - Flammable liquid and vapour. Flam. Liq. 3: H335 - May cause damage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H337 - May cause damage to organs through prolonged or repeated exposure. STOT RE 2: H337 - May cause drowsiness or dizziness. CLassification procedure: Skin Irrit. 2: Calculation method STOT RE 2: Calculation method <			
H319: Causes serious eye initiation. Texts of the legislative phrases mentioned in section 3: The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 CLP Regulation (EC) No 1272/2008: Acute Tox. 4: H312-H332 - Harmful in contact with skin or if inhaled. Acute Tox. 4: H312 - Harmful in contact with skin or if inhaled. Aquatic Chronic 3: H411 - Toxic to aquatic life with long lasting effects. Aquatic Chronic 3: H412 - Harmful in contact with skin or if inhaled. Aquatic Chronic 3: H412 - Harmful in contact with skin or if inhaled. Aquatic Chronic 3: H412 - Harmful in contact with long lasting effects. Aquatic Chronic 3: H412 - Harmful in aquatic life with long lasting effects. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Aquatic Chronic 2: H413 - Gauses serious eye irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Rept. 2: H326 - Flammable liquid and vapour. Rept. 2: H321 - Auge cause damage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H335 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H335 - May cause damage to argans through prolonged or repeated exposure. STOT SE 3: H335 - May cause damage to argans through prolonged or repeated exposure. Stori TFE 2: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method Aquatic Chronic 3: Calculation method Aquatic Chronic 3: Calculation method Apper 2: Ca	H373: May cause damage H361d: Suspected of dama H304: May be fatal if swall	to organs through prolonged iging the unborn child. owed and enters airways.	
The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 CLP Regulation (EC) No 1272/2008: Acute Tox. 4: H312-H332 - Harmful in contact with skin or if inhaled. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Aquatic Chronic 3: H412 - Noi: to aquatic life with long lasting effects. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Aquatic Chronic 2: H412 - Harmful to aquatic life with long lasting effects. App. Tox. 1: H304 - May be fatal if swallowed and enters airways. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 2: H225 - Filamnable liquid and vapour. Flam. Liq. 2: H226 - Filamnable liquid and vapour. Repr. 2: H361d - Suspected of damaging the unborn child. Skin Irrit. 2: H315 - Causes skin irritation. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H335 - May cause drowsiness or dizziness. Classification procedure: Skin Irrit. 2: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method STOT RE 2: Calculation method STOT RE 2: Calculation method Apue Chronic 3: Calculation method Apue Chronic 3: Calculation method Apue Chronic 4: Calculation method Apue Chronic 4: Calculation method Apue Chronic 4: Calculation method Apue Chronic 2: Calculation method Apue Chronic 2: Calculation method Apue Chronic 2: Calculation method Apue Chronic 5: Calculation method Apue Chronic 5			
individual components which appear in section 3 CLP Regulation (EC) No 1272/2008: Acute Tox. 4: H312-H332 - Harmful in contact with skin or if inhaled. Acute Tox. 4: H312 - Harmful if inhaled. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Aquatic 2: H319 - Causes serious eye irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Flam. Liq. 3: H226 - Flammable liquid and vapour. Flam. Liq. 3: H226 - Flammable liquid and vapour. Repr. 2: H3616 - Suspected of damaging the unborn child. Skin Irrit. 2: H315 - Causes skin irritation. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H335 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H335 - May cause drowsiness or dizziness. Classification procedure: Skin Irrit. 2: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method STOT SE 2: Calculation method STOT RE 2: Calculation method Aquatic Chronic 3: Calculation method App. 70x. 1: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://euh.europa.eu			
Acute Tox. 4: H312+H32 - Harmful in contact with skin or if inhaled. Acute Tox. 4: H332 - Harmful if inhaled. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Flam. Liq. 3: H226 - Flammable liquid and vapour. Rept. 2: H3161 - Suspected of damaging the unborn child. Skin Irrit. 2: H315 - Causes skin irritation. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H336 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H336 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H336 - May cause drowsiness or dizziness. Classification procedure: Skin Irrit. 2: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method STOT RE 2: Calculation method STOT RE 2: Calculation method Aquatic Chronic 3: Calculation method STOT RE 2: Calculation method Aquatic Chronic 3: Calculation method Asp. Tox. 1: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://edm-lex.europa.eu	individual components whi	ch appear in section 3	; they are present merely for informative purposes and refer to the
Acute Tox. 4: H332 - Harmful if inhaled. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Repr. 2: H361d - Suspected of damaging the unborn child. Skin Irrit. 2: H315 - Causes skin irritation. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Classification procedure: Skin Irrit. 2: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method STOT RE 2: Calculation method STOT RE 2: Calculation method STOT RE 2: Calculation method Aquatic Chronic 3: Calculation method STOT RE 2: Calculation method STOT RE 2: Calculation method Asp. Tox. 1: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://ekn-europa.eu		•	in or if inhaled
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Repr. 2: H361d - Suspected of damaging the unborn child. Skin Irrit. 2: H315 - Causes skin irritation. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H335 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H335 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H336 - May cause drowsiness or dizziness. Classification procedure: Skin Irrit. 2: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method STOT RE 2: Calculation method STOT RE 2: Calculation method STOT RE 2: Calculation method STOT RE 2: Calculation method Aquatic Chronic 3: Calculation method Aputic Chronic 3: Calculation method Aputic Chronic 3: Calculation method App. Tox. 1: Calculation method Asp. Tox. 1: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://exh.europa.eu	Acute Tox. 4: H332 - Harm	ful if inhaled.	
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.Eye Irrit. 2: H319 - Causes serious eye irritation.Flam. Liq. 2: H225 - Highly flammable liquid and vapour.Flam. Liq. 3: H226 - Flammable liquid and vapour.Repr. 2: H3614 - Suspected of damaging the unborn child.Skin Irrit. 2: H315 - Causes skin irritation.STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.STOT SE 2: H335 - May cause emagratory irritation.STOT SE 3: H336 - May cause damage to organs through prolonged or repeated exposure.STOT SE 3: H336 - May cause damage to organs through prolonged or repeated exposure.STOT SE 3: H336 - May cause damage to organs through prolonged or repeated exposure.STOT SE 3: H336 - May cause darouser organs through prolonged or repeated exposure.STOT SE 3: H336 - May cause darouser organs through prolonged or repeated exposure.STOT SE 3: H336 - May cause darouser organs through prolonged or repeated exposure.STOT SE 3: H336 - May cause darouser organs through prolonged or repeated exposure.STOT SE 3: H336 - May cause darouser or dizenters.Classification procedure:Skin Irrit. 2: Calculation methodSTOT SE 3: Calculation methodSTOT SE 2: Calculation methodAquatic Chronic 3: Calculation methodAge, z: Calculation methodRepr. 2: Calculation methodRepr. 2: Calculation methodAsp. Tox. 1: Calculation methodAsp. Tox. 1: Calculation methodAdvice related to training:Training is recommended			
Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Flam. Liq. 3: H226 - Flammable liquid and vapour. Repr. 2: H361d - Suspected of damaging the unborn child. Skin Irrit. 2: H315 - Causes skin irritation. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H335 - May cause drowsiness or dizziness. Classification procedure: Skin Irrit. 2: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method STOT RE 2: Calculation method Aquatic Chronic 3: Calculation method STOT RE 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu			
 Flam. Liq. 3: H226 - Flammable liquid and vapour. Repr. 2: H361d - Suspected of damaging the unborn child. Skin Irrit. 2: H315 - Causes skin irritation. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H335 - May cause respiratory irritation. STOT STO SE 3: H336 - May cause drowsiness or dizziness. Classification procedure: Skin Irrit. 2: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method STOT RE 2: Calculation method Stor RE 2: Calculation method Stor RE 2: Calculation method Stor RE 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://cua.europa.eu http://cua.europa.eu 	Eye Irrit. 2: H319 - Causes	serious eye irritation.	
Repr. 2: H361d - Suspected of damaging the unborn child. Skin Irrit. 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H335 - May cause drowsiness or dizziness. Classification procedure: Skin Irrit. 2: Calculation method STOT RE 2: Alardiant STOT SE 3: Calculation method STOT SE 3: Calculation method STOT RE 2: Calculation method STOT RE 2: Calculation method STOT SE 3: Calculation method STOT RE 2: Calculation method Repr. 2: Calculation method Repr. 2: Calculation method Repr. 2: Calculation method Flam. Liq. 2: Calculation method Repr. 1: Calculation method			ur.
Skin Irrit. 2: H315 - Čauses skin irritation. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Classification procedure: Skin Irrit. 2: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method STOT RE 2: Calculation method Repr. 2: Calculation method Asp. Tox. 1: Calculation method Asp. Tox. 1: Calculation method Flam. Liq. 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu			hild
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Classification procedure: Skin Irrit. 2: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method STOT RE 2: Calculation method Repr. 2: Calculation method Asp. Tox. 1: Calculation method Flam. Lig. 2: Calculation method Flam. Lig. 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: <			ind.
 STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Classification procedure: Skin Irrit. 2: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method Aquatic Chronic 3: Calculation method STOT RE 2: Calculation method Repr. 2: Calculation method Asp. Tox. 1: Calculation method Flam. Liq. 2: Calculation method Eye Irrit. 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://echa.europa.eu 			ugh prolonged or repeated exposure (Oral).
STOT SE 3: H336 - May cause drowsiness or dizziness. Classification procedure: Skin Irrit. 2: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method Aquatic Chronic 3: Calculation method STOT RE 2: Calculation method Repr. 2: Calculation method Asp. Tox. 1: Calculation method Flam. Liq. 2: Calculation method (2.6.4.3) Eye Irrit. 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu			ugh prolonged or repeated exposure.
Classification procedure: Skin Irrit. 2: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method Aquatic Chronic 3: Calculation method STOT RE 2: Calculation method Repr. 2: Calculation method Repr. 2: Calculation method Flam. Liq. 2: Calculation method Flam. Liq. 2: Calculation method Key Pirit. 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu			
Skin Irrit. 2: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method Aquatic Chronic 3: Calculation method STOT RE 2: Calculation method STOT RE 2: Calculation method Repr. 2: Calculation method Asp. Tox. 1: Calculation method Flam. Liq. 2: Calculation method Flam. Liq. 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu			
STOT SE 3: Calculation method STOT SE 3: Calculation method Aquatic Chronic 3: Calculation method STOT RE 2: Calculation method STOT RE 2: Calculation method Repr. 2: Calculation method Asp. Tox. 1: Calculation method Flam. Liq. 2: Calculation method Flam. Liq. 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://echa.europa.eu	-		
STOT SE 3: Calculation method Aquatic Chronic 3: Calculation method STOT RE 2: Calculation method STOT RE 2: Calculation method Repr. 2: Calculation method Asp. Tox. 1: Calculation method Flam. Liq. 2: Calculation method Flam. Liq. 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu			
STOT RE 2: Calculation method STOT RE 2: Calculation method Repr. 2: Calculation method Asp. Tox. 1: Calculation method Flam. Liq. 2: Calculation method (2.6.4.3) Eye Irrit. 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu			
STOT RE 2: Calculation method Repr. 2: Calculation method Asp. Tox. 1: Calculation method Flam. Liq. 2: Calculation method (2.6.4.3) Eye Irrit. 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu			
Repr. 2: Calculation method Asp. Tox. 1: Calculation method Flam. Liq. 2: Calculation method (2.6.4.3) Eye Irrit. 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu			
Asp. Tox. 1: Calculation method Flam. Liq. 2: Calculation method (2.6.4.3) Eye Irrit. 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu			
 Flam. Liq. 2: Calculation method (2.6.4.3) Eye Irrit. 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu 			
Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu			
Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu	Eye Irrit. 2: Calculation me	thod	
interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu		-	
http://echa.europa.eu http://eur-lex.europa.eu	interpretation of this safety	data sheet, as well as the la	
http://eur-lex.europa.eu		sources:	
		ıyms:	

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific PROFIRS

legislation 0RS390-0.5L

Date of compilation: 14/10/2021	Revised: 03/03/2023	Version: 2 (Replaced 1)
SECTION 16: OTHER INFORM	MATION ** (continued)	
ADR: European agreement IMDG: International maritin IATA: International Air Trar ICAO: International Civil Av COD: Chemical Oxygen De BOD5: 5day biochemical ox BCF: Bioconcentration facto LD50: Lethal Dose 50 LC50: Lethal Concentration EC50: Effective concentration EC50: Effective concentration LogPOW: Octanolwater par Koc: Partition coefficient of UFI: unique formula identifi IARC: International Agency	me dangerous goods code nsport Association viation Organisation mand xygen demand or 1 50 ton 50 rtition coefficient 5 organic carbon fier	l carriage of dangerous goods by road

** Changes with regards to the previous version

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.