

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS410P-1L

Date of compilation: 14/10/2021 Revised: 01/03/2023 Version: 2 (Replaced 1)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: ORS410P-1L

Other means of identification:

UFI: NNC6-207Y-M003-KWK0

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Top. For professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Inter Cars S.A. ul. Powsińska 64 02-903 Warszawa - Polska kontakt@intercars.com www.intercars.com

1.4 Emergency telephone number:

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Asp. Tox. 1: Aspiration hazard, Category 1, H304 Eye Dam. 1: Serious eye damage, Category 1, H318 Flam. Liq. 3: Flammable liquids, Category 3, H226 Skin Irrit. 2: Skin irritation, Category 2, H315

Skin Sens. 1A: Sensitisation, skin, Category 1A, H317

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger









Hazard statements:

H226 - Flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H336 - May cause drowsiness or dizziness.

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

Contains maleic anhydride.

Substances that contribute to the classification

N-butyl acetate; Xylene; 2-methoxy-1-methylethyl acetate; butan-1-ol

^{**} Changes with regards to the previous version



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS410P-1L

Date of compilation: 14/10/2021 Revised: 01/03/2023 Version: 2 (Replaced 1)

SECTION 2: HAZARDS IDENTIFICATION ** (continued)

UFI: NNC6-207Y-M003-KWK0

Additional labeling:

V.O.C. 2004/42/WE IIB(e) (840) 762

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration	
CAS: EC:	123-86-4 204-658-1	N-butyl acetate(1)	ATP CLP00		
Index:	607-025-00-1 01-2119485493-29- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	58 - <68 %	
CAS: EC:	1330-20-7 215-535-7	Xylene ⁽¹⁾	Self-classified		
Index:	601-022-00-9 01-2119488216-32- XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	<10 %	
CAS: EC:	108-65-6 203-603-9	2-methoxy-1-methy	lethyl acetate ⁽¹⁾ Self-classified		
Index:	203-603-9 607-195-00-7 01-2119475791-29- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	2,5 - <10 %	
	71-36-3	butan-1-ol ⁽¹⁾	Self-classified		
Index:	EC: 200-751-6 Index: 603-004-00-6 REACH: 01-2119484630-38- XXXX	Regulation 1272/2008	Acute Tox. 4: H302; Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335; STOT SE 3: H336 - Danger	<5 %	
	112-07-2 203-933-3	2-butoxyethyl acetate ⁽¹⁾ ATP CLP0			
	203-933-3 607-038-00-2 01-2119475112-47- XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332 - Warning	<3 %	
CAS:	100-41-4	Ethylbenzene(1)	Self-classified		
	202-849-4 601-023-00-4 01-2119489370-35- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	<2 %	
CAS: EC:	100-41-4 202-849-4	Ethylbenzene(2)	ATP ATP06		
Index:	601-023-00-4 01-2119489370-35- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	<1 %	
CAS:	50-00-0	Formaldehyde (2)	ATP ATP06		
	200-001-8 605-001-00-5 01-2119488953-20- XXXX	Regulation 1272/2008	Acute Tox. 3: H301+H311+H331; Carc. 1B: H350; Muta. 2: H341; Skin Corr. 1B: H314; Skin Sens. 1: H317 - Danger	<1 %	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

^{**} Changes with regards to the previous version

⁽²⁾ Substance with a Union workplace exposure limit

^{**} Changes with regards to the previous version



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS410P-1L

Date of compilation: 14/10/2021 Revised: 01/03/2023 Version: 2 (Replaced 1)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

	Identification		Chemical name/Classification			
CAS:	121-44-8	triethylamine(2)	Self-classified			
	204-469-4 612-004-00-5 01-2119475467-26- XXXX	Regulation 1272/2008	Acute Tox. 3: H311+H331; Acute Tox. 4: H302; Eye Dam. 1: H318; Flam. Liq. 2: H225; Skin Corr. 1A: H314; STOT SE 3: H335 - Danger	. <1 %		
CAS:	108-31-6	maleic anhydride(1)	ATP ATP13			
	203-571-6 607-096-00-9 01-2119472428-31- XXXX	Regulation 1272/2008	Acute Tox. 4: H302; Eye Dam. 1: H318; Resp. Sens. 1: H334; Skin Corr. 1B: H314; Skin Sens. 1A: H317; STOT RE 1: H372; EUH071 - Danger	<1 %		

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identific	cation	Specific concentration limit
Formaldehyde CAS: 50-00-0 EC: 200-001-8		% (w/w) >=25: Skin Corr. 1B - H314 5<= % (w/w) <25: Skin Irrit. 2 - H315 % (w/w) >=25: Eye Dam. 1 - H318 5<= % (w/w) <25: Eye Irrit. 2 - H319 % (w/w) >=0,2: Skin Sens. 1 - H317 % (w/w) >=5: STOT SE 3 - H335
triethylamine CAS: 121-44-8 EC: 204-469-4		% (w/w) >=1: STOT SE 3 - H335
maleic anhydride CAS: 108-31-6 EC: 203-571-6		% (w/w) >=0,001: Skin Sens. 1A - H317

^{**} Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

⁽²⁾ Substance with a Union workplace exposure limit



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS410P-1L

Date of compilation: 14/10/2021 Revised: 01/03/2023 Version: 2 (Replaced 1)

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS410P-1L

Date of compilation: 14/10/2021 Revised: 01/03/2023 Version: 2 (Replaced 1)

SECTION 7: HANDLING AND STORAGE (continued)

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 25 °C

Maximum time: 36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	O	ccupational exposu	ure limits
N-butyl acetate	IOELV (8h)	50 ppm	241 mg/m ³
CAS: 123-86-4 EC: 204-658-1	IOELV (STEL)	150 ppm	723 mg/m ³
Xylene	IOELV (8h)	50 ppm	221 mg/m ³
CAS: 1330-20-7 EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m ³
2-methoxy-1-methylethyl acetate	IOELV (8h)	50 ppm	275 mg/m ³
CAS: 108-65-6 EC: 203-603-9	IOELV (STEL)	100 ppm	550 mg/m ³
2-butoxyethyl acetate	IOELV (8h)	20 ppm	133 mg/m ³
CAS: 112-07-2 EC: 203-933-3	IOELV (STEL)	50 ppm	333 mg/m ³
Ethylbenzene	IOELV (8h)	100 ppm	442 mg/m ³
CAS: 100-41-4 EC: 202-849-4	IOELV (STEL)	200 ppm	884 mg/m ³
Ethylbenzene	IOELV (8h)	100 ppm	442 mg/m ³
CAS: 100-41-4 EC: 202-849-4	IOELV (STEL)	200 ppm	884 mg/m ³
Formaldehyde	IOELV (8h)	0,3 ppm	0,37 mg/m ³
CAS: 50-00-0 EC: 200-001-8	IOELV (STEL)	0,6 ppm	0,74 mg/m ³
triethylamine	IOELV (8h)	2 ppm	8,4 mg/m ³
CAS: 121-44-8 EC: 204-469-4	IOELV (STEL)	3 ppm	12,6 mg/m ³

DNEL (Workers):

		Short e	xposure	Long ex	xposure
Identification		Systemic	Local	Systemic	Local
N-butyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-86-4	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
EC: 204-658-1	Inhalation	600 mg/m ³	600 mg/m ³	300 mg/m ³	300 mg/m ³



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS410P-1L

Date of compilation: 14/10/2021 Revised: 01/03/2023 Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

			exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	550 mg/m ³	275 mg/m ³	Non-applicable
butan-1-ol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 71-36-3	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 200-751-6	Inhalation	Non-applicable	Non-applicable	Non-applicable	310 mg/m ³
2-butoxyethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 112-07-2	Dermal	120 mg/kg	Non-applicable	169 mg/kg	Non-applicable
EC: 203-933-3	Inhalation	Non-applicable	333 mg/m ³	133 mg/m ³	Non-applicable
Ethylbenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
Ethylbenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
Formaldehyde	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 50-00-0	Dermal	Non-applicable	Non-applicable	240 mg/kg	Non-applicable
EC: 200-001-8	Inhalation	Non-applicable	0,75 mg/m ³	9 mg/m³	0,375 mg/m ³
triethylamine	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 121-44-8	Dermal	Non-applicable	Non-applicable	12,1 mg/kg	Non-applicable
EC: 204-469-4	Inhalation	12,6 mg/m ³	12,6 mg/m ³	8,4 mg/m ³	8,4 mg/m ³
maleic anhydride	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-31-6	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 203-571-6	Inhalation	0,2 mg/m ³	0,2 mg/m ³	0,081 mg/m ³	0,081 mg/m ³

DNEL (General population):

		Short	Short exposure		Long exposure	
Identification	Systemic	Local	Systemic	Local		
N-butyl acetate	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable	
CAS: 123-86-4	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable	
EC: 204-658-1	Inhalation	300 mg/m ³	300 mg/m ³	35,7 mg/m ³	35,7 mg/m ³	
Xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable	
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable	
EC: 215-535-7	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³	
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable	
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable	
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m ³	33 mg/m ³	
butan-1-ol	Oral	Non-applicable	Non-applicable	1,562 mg/kg	Non-applicable	
CAS: 71-36-3	Dermal	Non-applicable	Non-applicable	3,125 mg/kg	Non-applicable	
EC: 200-751-6	Inhalation	Non-applicable	Non-applicable	55,357 mg/m ³	155 mg/m ³	
2-butoxyethyl acetate	Oral	36 mg/kg	Non-applicable	8,6 mg/kg	Non-applicable	
CAS: 112-07-2	Dermal	72 mg/kg	Non-applicable	102 mg/kg	Non-applicable	
EC: 203-933-3	Inhalation	Non-applicable	200 mg/m ³	80 mg/m ³	Non-applicable	
Ethylbenzene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable	
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable	



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS410P-1L

Date of compilation: 14/10/2021 Revised: 01/03/2023 Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Ethylbenzene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable
Formaldehyde	Oral	Non-applicable	Non-applicable	4,1 mg/kg	Non-applicable
CAS: 50-00-0	Dermal	Non-applicable	Non-applicable	102 mg/kg	Non-applicable
EC: 200-001-8	Inhalation	Non-applicable	Non-applicable	3,2 mg/m ³	0,1 mg/m ³

PNEC:

Identification				
N-butyl acetate	STP	35,6 mg/L	Fresh water	0,18 mg/L
CAS: 123-86-4	Soil	0,09 mg/kg	Marine water	0,018 mg/L
EC: 204-658-1	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg
Xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0,635 mg/L
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water	0,064 mg/L
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
butan-1-ol	STP	2476 mg/L	Fresh water	0,082 mg/L
CAS: 71-36-3	Soil	0,017 mg/kg	Marine water	0,008 mg/L
EC: 200-751-6	Intermittent	2,25 mg/L	Sediment (Fresh water)	0,324 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,032 mg/kg
2-butoxyethyl acetate	STP	90 mg/L	Fresh water	0,304 mg/L
CAS: 112-07-2	Soil	0,415 mg/kg	Marine water	0,03 mg/L
EC: 203-933-3	Intermittent	0,56 mg/L	Sediment (Fresh water)	2,03 mg/kg
	Oral	0,06 g/kg	Sediment (Marine water)	0,203 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg
Formaldehyde	STP	0,19 mg/L	Fresh water	0,44 mg/L
CAS: 50-00-0	Soil	0,2 mg/kg	Marine water	0,44 mg/L
EC: 200-001-8	Intermittent	4,44 mg/L	Sediment (Fresh water)	2,3 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	2,3 mg/kg
triethylamine	STP	100 mg/L	Fresh water	0,11 mg/L
CAS: 121-44-8	Soil	0,25 mg/kg	Marine water	0,011 mg/L
EC: 204-469-4	Intermittent	0,08 mg/L	Sediment (Fresh water)	1,575 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,158 mg/kg
maleic anhydride	STP	44,6 mg/L	Fresh water	0,038 mg/L
CAS: 108-31-6	Soil	0,037 mg/kg	Marine water	0,004 mg/L
EC: 203-571-6	Intermittent	0,379 mg/L	Sediment (Fresh water)	0,296 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,03 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS410P-1L

Date of compilation: 14/10/2021 Revised: 01/03/2023 Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	CAT III	EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CATII	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Antistatic and fireproof protective clothing	CAT III	EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
Mandatory foot protection	Safety footwear with antistatic and heat resistant properties	CAT III	EN ISO 13287:2020 EN ISO 20345:2011	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
•	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	*	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

*Not relevant due to the nature of the product, not providing information property of its hazards.



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS410P-1L

Date of compilation: 14/10/2021 Revised: 01/03/2023 Version: 2 (Replaced 1)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Appearance:

Physical state at 20 °C:

Appearance:

Fluid

Colour:

Colourless

Odour:

Characteristic

Odour threshold:

Non-applicable *

Volatility:

Boiling point at atmospheric pressure: 129 °C
Vapour pressure at 20 °C: 1184 Pa

Vapour pressure at 50 °C: 5759,12 Pa (5,76 kPa) Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: 910 - 920 kg/m³ Relative density at 20 °C: 0,91 - 0,92 Dynamic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 40 °C: <20,5 mm²/s Concentration: Non-applicable * pH: Non-applicable * Vapour density at 20 °C: Non-applicable * Partition coefficient n-octanol/water 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Solubility properties: Non-applicable * Decomposition temperature: Non-applicable * Melting point/freezing point: Non-applicable *

Flammability:

Flash Point: 27 °C

Flammability (solid, gas): Non-applicable *

Autoignition temperature: 215 °C

Lower flammability limit: Not available

Upper flammability limit: Not available

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Corrosive to metals:

Heat of combustion:

Aerosols-total percentage (by mass) of flammable

Non-applicable *

Non-applicable *

Non-applicable *

components:

Other safety characteristics:

Surface tension at 20 °C:

Refraction index:

Non-applicable *

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS410P-1L

Date of compilation: 14/10/2021 Revised: 01/03/2023 Version: 2 (Replaced 1)

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION **

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
 - IARC: Formaldehyde (1); Xylene (3); Ethylbenzene (2B); Ethylbenzene (2B); Hydrocarbons, C9, aromatics (3)
 - Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
 - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

^{**} Changes with regards to the previous version



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS410P-1L

Date of compilation: 14/10/2021 Revised: 01/03/2023 Version: 2 (Replaced 1)

SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute t	oxicity	Genus	
Xylene	LD50 oral 21	L00 mg/kg	Rat	
CAS: 1330-20-7	LD50 dermal 11	L00 mg/kg	Rat	
EC: 215-535-7	LC50 inhalation 11	l mg/L (ATEi)		
butan-1-ol	LD50 oral 50	00 mg/kg (ATEi)		
CAS: 71-36-3	LD50 dermal 34	100 mg/kg	Rabbit	
EC: 200-751-6	LC50 inhalation 24	1,66 mg/L (4 h)	Rat	
Ethylbenzene	LD50 oral 35	500 mg/kg	Rat	
CAS: 100-41-4	LD50 dermal 15	5354 mg/kg	Rabbit	
EC: 202-849-4	LC50 inhalation 17	7,2 mg/L (4 h)	Rat	
N-butyl acetate	LD50 oral 12	2789 mg/kg	Rat	
CAS: 123-86-4	LD50 dermal 14	1112 mg/kg	Rabbit	
EC: 204-658-1	LC50 inhalation 23	3,4 mg/L (4 h)	Rat	
2-butoxyethyl acetate	LD50 oral 21	L00 mg/kg	Rat	
CAS: 112-07-2	LD50 dermal 14	180 mg/kg	Rabbit	
EC: 203-933-3	LC50 inhalation 11	L mg/L (4 h)	Rat	
2-methoxy-1-methylethyl acetate	LD50 oral 85	532 mg/kg	Rat	
CAS: 108-65-6	LD50 dermal >5	5000 mg/kg	Rat	
EC: 203-603-9	LC50 inhalation 30) mg/L (4 h)	Rat	
Ethylbenzene	LD50 oral 35	500 mg/kg	Rat	
CAS: 100-41-4	LD50 dermal 15	5354 mg/kg	Rabbit	
EC: 202-849-4	LC50 inhalation 17	7,2 mg/L (4 h)	Rat	
Formaldehyde	LD50 oral 10	00 mg/kg		
CAS: 50-00-0	LD50 dermal 30	00 mg/kg		
EC: 200-001-8	LC50 inhalation No	on-applicable		
triethylamine	LD50 oral 73	30 mg/kg	Rat	
CAS: 121-44-8	LD50 dermal 58	30 mg/kg	Rabbit	
EC: 204-469-4	LC50 inhalation No	on-applicable		

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

^{**} Changes with regards to the previous version

^{**} Changes with regards to the previous version



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS410P-1L

Date of compilation: 14/10/2021 Revised: 01/03/2023 Version: 2 (Replaced 1)

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
N-butyl acetate	LC50	Non-applicable		
CAS: 123-86-4	EC50	Non-applicable		
EC: 204-658-1	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Xylene	LC50	>10 - 100 mg/L (96 h)		Fish
CAS: 1330-20-7	EC50	>10 - 100 mg/L (48 h)		Crustacean
EC: 215-535-7	EC50	>10 - 100 mg/L (72 h)		Algae
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
EC: 203-603-9	EC50	Non-applicable		
butan-1-ol	LC50	1740 mg/L (96 h)	Pimephales promelas	Fish
CAS: 71-36-3	EC50	1983 mg/L (48 h)	Daphnia magna	Crustacean
EC: 200-751-6	EC50	500 mg/L (96 h)	Scenedesmus subspicatus	Algae
2-butoxyethyl acetate	LC50	80 mg/L (48 h)	Leuciscus idus	Fish
CAS: 112-07-2	EC50	37 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-933-3	EC50	500 mg/L (72 h)	Scenedesmus subspicatus	Algae
Ethylbenzene	LC50	42,3 mg/L (96 h)	Pimephales promelas	Fish
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
Ethylbenzene	LC50	42,3 mg/L (96 h)	Pimephales promelas	Fish
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
Formaldehyde	LC50	100 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 50-00-0	EC50	42 mg/L (24 h)	Daphnia magna	Crustacean
EC: 200-001-8	EC50	Non-applicable		
triethylamine	LC50	43,7 mg/L (96 h)	Pimephales promelas	Fish
CAS: 121-44-8	EC50	200 mg/L (48 h)	Daphnia magna	Crustacean
EC: 204-469-4	EC50	Non-applicable		

Chronic toxicity:

Identification		Concentration	Species	Genus
N-butyl acetate	NOEC	Non-applicable		
CAS: 123-86-4 EC: 204-658-1	NOEC	23,2 mg/L	Daphnia magna	Crustacean
Xylene	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
CAS: 1330-20-7 EC: 215-535-7	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
2-methoxy-1-methylethyl acetate	NOEC	47,5 mg/L	Oryzias latipes	Fish
CAS: 108-65-6 EC: 203-603-9	NOEC	100 mg/L	Daphnia magna	Crustacean
butan-1-ol	NOEC	Non-applicable		
CAS: 71-36-3 EC: 200-751-6	NOEC	4,1 mg/L	Daphnia magna	Crustacean
Ethylbenzene	NOEC	Non-applicable		
CAS: 100-41-4 EC: 202-849-4	NOEC	0,96 mg/L	Ceriodaphnia dubia	Crustacean
Ethylbenzene	NOEC	Non-applicable		
CAS: 100-41-4 EC: 202-849-4	NOEC	0,96 mg/L	Ceriodaphnia dubia	Crustacean
Formaldehyde	NOEC	Non-applicable		
CAS: 50-00-0 EC: 200-001-8	NOEC	6,4 mg/L	Daphnia magna	Crustacean
triethylamine	NOEC	Non-applicable		
CAS: 121-44-8 EC: 204-469-4	NOEC	11 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

^{**} Changes with regards to the previous version



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS410P-1L

Date of compilation: 14/10/2021 Revised: 01/03/2023 Version: 2 (Replaced 1)

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Substance-specific information:

Identification	De	gradability	Biode	egradability
N-butyl acetate	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 123-86-4	COD	Non-applicable	Period	5 days
EC: 204-658-1	BOD5/COD	Non-applicable	% Biodegradable	84 %
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L
CAS: 108-65-6	COD	Non-applicable	Period	8 days
EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
butan-1-ol	BOD5	1,71 g O2/g	Concentration	Non-applicable
CAS: 71-36-3	COD	2,46 g O2/g	Period	19 days
EC: 200-751-6	BOD5/COD	0,7	% Biodegradable	98 %
2-butoxyethyl acetate	BOD5	Non-applicable	Concentration	30 mg/L
CAS: 112-07-2	COD	Non-applicable	Period	28 days
EC: 203-933-3	BOD5/COD	Non-applicable	% Biodegradable	77,3 %
Ethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-41-4	COD	Non-applicable	Period	14 days
EC: 202-849-4	BOD5/COD	Non-applicable	% Biodegradable	90 %
Ethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-41-4	COD	Non-applicable	Period	14 days
EC: 202-849-4	BOD5/COD	Non-applicable	% Biodegradable	90 %
Formaldehyde	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 50-00-0	COD	Non-applicable	Period	14 days
EC: 200-001-8	BOD5/COD	Non-applicable	% Biodegradable	92 %
triethylamine	BOD5	Non-applicable	Concentration	26 mg/L
CAS: 121-44-8	COD	Non-applicable	Period	28 days
EC: 204-469-4	BOD5/COD	Non-applicable	% Biodegradable	85 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification		Bioaccun	nulation potential
N-butyl acetate	BC	CF .	4
CAS: 123-86-4	Por	ow Log	1.78
EC: 204-658-1	Poi	otential	Low
Xylene	BC	CF .	9
CAS: 1330-20-7	Por	ow Log	2.77
EC: 215-535-7	Poi	otential	Low
2-methoxy-1-methylethyl acetate	BC	CF .	1
CAS: 108-65-6	Por	ow Log	0.43
EC: 203-603-9	Poi	otential	Low
butan-1-ol	BC	CF .	1
CAS: 71-36-3	Por	ow Log	0.88
EC: 200-751-6	Poi	otential	Low
2-butoxyethyl acetate	BC	CF .	3
CAS: 112-07-2	Po	w Log	1.51
EC: 203-933-3	Pot	otential	Low
Ethylbenzene	BC	CF .	1
CAS: 100-41-4	Po	ow Log	3.15
EC: 202-849-4	Pot	otential	Low

^{**} Changes with regards to the previous version



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS410P-1L

Date of compilation: 14/10/2021 Revised: 01/03/2023 Version: 2 (Replaced 1)

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Identification	Bioaccu	mulation potential
Ethylbenzene	BCF	1
CAS: 100-41-4	Pow Log	3.15
EC: 202-849-4	Potential	Low
Formaldehyde	BCF	3
CAS: 50-00-0	Pow Log	0.35
EC: 200-001-8	Potential	Low
triethylamine	BCF	5
CAS: 121-44-8	Pow Log	1.45
EC: 204-469-4	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volat	ility
N-butyl acetate	Koc	Non-applicable	Henry	Non-applicable
CAS: 123-86-4	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 204-658-1	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable
Xylene	Koc	202	Henry	524,86 Pa·m³/mol
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes
butan-1-ol	Koc	2.44	Henry	5,39E-2 Pa·m³/mol
CAS: 71-36-3	Conclusion	Very High	Dry soil	Yes
EC: 200-751-6	Surface tension	2,567E-2 N/m (25 °C)	Moist soil	Yes
2-butoxyethyl acetate	Koc	Non-applicable	Henry	5,532E-1 Pa·m³/mol
CAS: 112-07-2	Conclusion	Non-applicable	Dry soil	No
EC: 203-933-3	Surface tension	Non-applicable	Moist soil	Yes
Ethylbenzene	Koc	520	Henry	798,44 Pa·m³/mol
CAS: 100-41-4	Conclusion	Moderate	Dry soil	Yes
EC: 202-849-4	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes
Ethylbenzene	Koc	520	Henry	798,44 Pa·m³/mol
CAS: 100-41-4	Conclusion	Moderate	Dry soil	Yes
EC: 202-849-4	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes
Formaldehyde	Koc	Non-applicable	Henry	Non-applicable
CAS: 50-00-0	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 200-001-8	Surface tension	1,416E-2 N/m (25 °C)	Moist soil	Non-applicable
triethylamine	Koc	145	Henry	Non-applicable
CAS: 121-44-8	Conclusion	Very High	Dry soil	Non-applicable
EC: 204-469-4	Surface tension	2,024E-2 N/m (25 °C)	Moist soil	Non-applicable
maleic anhydride	Koc	Non-applicable	Henry	Non-applicable
CAS: 108-31-6	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 203-571-6	Surface tension	1,673E-2 N/m (250,21 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

^{**} Changes with regards to the previous version



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS410P-1L

Date of compilation: 14/10/2021 Revised: 01/03/2023 Version: 2 (Replaced 1)

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Code	Description	Waste class (Regulation (EU) No 1357/2014)
	It is not possible to assign a specific code, as it depends on the intended use by the user	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

14.1 UN number or ID number:

er: UN1993

14.2 UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (N-butyl acetate)

14.3 Transport hazard class(es): 3Labels: 314.4 Packing group: III

14.4 Packing group: III

14.5 Environmental hazards: No

14.6 Special precautions for user

Special regulations: 274, 601
Tunnel restriction code: D/E

Physico-Chemical properties: see section 9

Limited quantities: 5 L

14.7 Maritime transport in bulk according to IMO

instruments:

Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:

14.1 UN number or ID number: UN1993

14.2 UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (N-butyl acetate)

14.3 Transport hazard class(es): 3
Labels: 3
14.4 Packing group: III

14.4 Packing group: III **14.5 Marine pollutant:** No

14.6 Special precautions for user

Special regulations: 274, 223, 955 EmS Codes: F-E, S-E Physico-Chemical properties: see section 9

Limited quantities: 5 L

Segregation group: Non-applicable **14.7 Maritime transport in bulk** Non-applicable

according to IMO instruments:

instruments:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2022:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS410P-1L

Date of compilation: 14/10/2021 Revised: 01/03/2023 Version: 2 (Replaced 1)

SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number or ID number: UN1993

14.2 UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (N-butyl acetate)

14.3 Transport hazard class(es): 3 Labels: 3

14.4 Packing group: III
14.5 Environmental hazards: No
14.6 Special precautions for user

Physica-Chemical properties:

Physico-Chemical properties: see section 9 **14.7 Maritime transport in bulk** Non-applicable

according to IMO instruments:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Formaldehyde (Product-type 2, 3, 22)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS410P-1L

Date of compilation: 14/10/2021 Revised: 01/03/2023 Version: 2 (Replaced 1)

SECTION 16: OTHER INFORMATION (continued)

COMMISSION REGULATION (EU) 2020/878

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

- · New declared substances
 - 2-methoxy-1-methylethyl acetate (108-65-6)
- · Removed substances
 - 2-methoxy-1-methylethyl acetate (108-65-6)

Substances that contribute to the classification (SECTION 2):

- New declared substances
 - 2-methoxy-1-methylethyl acetate (108-65-6)
- · Removed substances

Ethylbenzene (100-41-4)

Texts of the legislative phrases mentioned in section 2:

- H336: May cause drowsiness or dizziness.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H317: May cause an allergic skin reaction.
- H304: May be fatal if swallowed and enters airways.
- H226: Flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

- Acute Tox. 3: H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.
- Acute Tox. 3: H311+H331 Toxic in contact with skin or if inhaled.
- Acute Tox. 4: H302 Harmful if swallowed.
- Acute Tox. 4: H312+H332 Harmful in contact with skin or if inhaled.
- Acute Tox. 4: H332 Harmful if inhaled.
- Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects.
- Asp. Tox. 1: H304 May be fatal if swallowed and enters airways.
- Carc. 1B: H350 May cause cancer.
- Eye Dam. 1: H318 Causes serious eye damage.
- Eye Irrit. 2: H319 Causes serious eye irritation.
- Flam. Liq. 2: H225 Highly flammable liquid and vapour.
- Flam. Liq. 3: H226 Flammable liquid and vapour.
- Muta. 2: H341 Suspected of causing genetic defects.
- Resp. Sens. 1: H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Skin Corr. 1A: H314 Causes severe skin burns and eye damage.
- Skin Corr. 1B: H314 Causes severe skin burns and eye damage.
- Skin Irrit. 2: H315 Causes skin irritation.
- Skin Sens. 1: H317 May cause an allergic skin reaction.
- Skin Sens. 1A: H317 May cause an allergic skin reaction.
- STOT RE 1: H372 Causes damage to organs through prolonged or repeated exposure (Inhalation).
- STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure (Inhalation).
- STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure (Oral).
- STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure.
- STOT SE 3: H335 May cause respiratory irritation.
- STOT SE 3: H336 May cause drowsiness or dizziness.

Classification procedure:

- STOT SE 3: Calculation method
- Skin Irrit. 2: Calculation method
- Eye Dam. 1: Calculation method
- Skin Sens. 1A: Calculation method
- Asp. Tox. 1: Calculation method Flam. Lig. 3: Calculation method (2.6.4.3)

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

0RS410P-1L

Date of compilation: 14/10/2021 Revised: 01/03/2023 Version: 2 (Replaced 1)

SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50

LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.