Date printed 16.02.2023, Revision 16.02.2023



Version 12.0. Supersedes version: 11.0 Page 1 / 16

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

hydraulic fluid

Article number: 21647 UFI: 3HXW-H12E-000T-2DJE

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Hydraulics oil

1.2.2 Uses advised against

None known.

# 1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG

Wilhelmstr. 47

58256 Ennepetal / GERMANY Phone +49 2333 911-0 Fax +49 2333 911-444 Homepage www.febi.com E-mail info@febi.com

Address enquiries to

Technical information info@febi.com
Safety Data Sheet info@febi.com

1.4 Emergency telephone number

**Advisory body** +49 (0)89-19240 (24h) (English)

Company +49 2333 911-0

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

Acute Tox. 4: H332 Harmful if inhaled.

Asp. Tox. 1: H304 May be fatal if swallowed and enters airways. Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Hazard pictograms

The product is required to be labelled in accordance with regulation CLP.





Signal word DANGER

Contains: 1-Decene, Dimer, hydrogenated

**Hazard statements** H332 Harmful if inhaled.

H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements** P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

 ${\tt P301+P310\ IF\ SWALLOWED:\ Immediately\ call\ a\ POISON\ CENTER\ /\ doctor.}$ 

P312 Call a POISON CENTER / doctor if you feel unwell.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents / container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of

disposal.

**Special labelling**Contains: Methyl methacrylate. EUH208 May produce an allergic reaction.

### Ferdinand Bilstein GmbH + Co. KG

Date printed 16.02.2023, Revision 16.02.2023



Version 12.0. Supersedes version: 11.0 Page 2 / 16

#### 2.3 Other hazards

**Human health dangers** Frequent persistent contact with the skin can cause skin irritation.

If swallowed or in the event of vomiting, risk of product entering the lungs.

**Environmental hazards** Does not contain any PBT or vPvB substances.

Contains no ingredients with endocrine-disrupting properties.

Other hazards Further hazards were not determined with the current level of knowledge.

### **SECTION 3: Composition / Information on ingredients**

#### 3.1 Substances

not applicable

### 3.2 Mixtures

# The product is a mixture.

Range [%]	Substance
50 - < 99	1-Decene, Dimer, hydrogenated
	CAS: 68649-11-6, EINECS/ELINCS: 500-228-5, Reg-No.: 01-2119493069-28-XXXX
	GHS/CLP: Acute Tox. 4: H332 - Asp. Tox. 1: H304
10 - < 20	Distillates (petroleum), hydrotreated light naphthenic
	CAS: 64742-53-6, EINECS/ELINCS: 265-156-6, EU-INDEX: 649-466-00-2, Reg-No.: 01-2119480375-34
	GHS/CLP: Asp. Tox. 1: H304
1 - < 10	Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, <0,03% aromatics
	CAS: 1174522-45-2, EINECS/ELINCS: 934-954-2, EU-INDEX: 649-422-00-2, Reg-No.: 01-2119826592-36-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 10	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based
	CAS: 72623-87-1, EINECS/ELINCS: 276-738-4, EU-INDEX: 649-483-00-5, Reg-No.: 01-2119474889-13-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 10	Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt)
	CAS: 64742-65-0, EINECS/ELINCS: 265-169-7, Reg-No.: 01-2119471299-27-XXXX
	GHS/CLP: Asp. Tox. 1: H304
0.25 - < 1	2,6-di-tert-butyl-p-cresol
	CAS: 128-37-0, EINECS/ELINCS: 204-881-4, Reg-No.: 01-2119565113-46-XXXX
	GHS/CLP: Aquatic Acute 1: H400 - Aquatic Chronic 1: H410,
	M-Factor (acute): 1, M-Factor (chronic): 1
0.1 - < 1	Methyl methacrylate
	CAS: 80-62-6, EINECS/ELINCS: 201-297-1, EU-INDEX: 607-035-00-6, Reg-No.: 01-2119452498-28-XXXX
	GHS/CLP: Flam. Liq. 2: H225 - STOT SE 3: H335 - Skin Irrit. 2: H315 - Skin Sens. 1: H317

**Comment on component parts** 

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.

For full text of H-statements: see SECTION 16.

### **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

General information Change soaked clothing.

**Inhalation** Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

Skin contact In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

**Eye contact**Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Ingestion Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Consult a doctor immediately.

Date printed 16.02.2023, Revision 16.02.2023



Page 3 / 16 Version 12.0. Supersedes version: 11.0

### Most important symptoms and effects, both acute and delayed

Symptoms of poisoning may not occur for many hours, therefore keep under medical supervision for at least 48 hours.

#### Indication of any immediate medical attention and special treatment needed 4.3

If swallowed or in the event of vomiting, risk of product entering the lungs.

Treat symptomatically.

Forward this sheet to your doctor.

### **SECTION 5: Fire-fighting measures**

### **Extinguishing media**

Suitable extinguishing media

Foam, dry powder, water spray jet, carbon dioxide

Extinguishing media that must not

be used

Full water jet

### Special hazards arising from the substance or mixture

Not combusted hydrocarbons.

Risk of formation of toxic pyrolysis products.

Carbon monoxide (CO)

### 5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

# **SECTION 6: Accidental release measures**

# Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.

Forms slippery surfaces with water.

# **Environmental precautions**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

### Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder). Dispose of absorbed material in accordance within the regulations.

### Reference to other sections

See SECTION 8+13

# **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Avoid formation of aerosols.

Do not eat, drink or smoke when using this product.

Use barrier skin cream.

Wash hands before breaks and after work.

Cloths contaminated with product should not be kept in trouser pockets. Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash before reuse.

# Ferdinand Bilstein GmbH + Co. KG

Date printed 16.02.2023, Revision 16.02.2023



Version 12.0. Supersedes version: 11.0

Page 4 / 16

# 7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container. Prevent penetration into the ground.

Do not store together with food and animal food/diet.

Keep container tightly closed.

Keep container in a well-ventilated place.

# 7.3 Specific end use(s)

See product use, SECTION 1.2

Date printed 16.02.2023, Revision 16.02.2023



Version 12.0. Supersedes version: 11.0 Page 5 / 16

# SECTION 8: Exposure controls / personal protection

# 8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance

Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, <0,03% aromatics

CAS: 1174522-45-2, EINECS/ELINCS: 934-954-2, EU-INDEX: 649-422-00-2, Reg-No.: 01-2119826592-36-XXXX

Long-term exposure: 1200 mg/m³

2,6-di-tert-butyl-p-cresol

CAS: 128-37-0, EINECS/ELINCS: 204-881-4, Reg-No.: 01-2119565113-46-XXXX

Long-term exposure: 10 mg/m<sup>3</sup>

### **DNEL**

Substance
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
Industrial, inhalative, Long-term - local effects, 5.4 mg/m³
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, <0,03% aromatics, CAS: 1174522-45-2
There are no DNEL values established for the substance.
1-Decene, Dimer, hydrogenated, CAS: 68649-11-6
Industrial, inhalative, Acute - systemic effects, 60 mg/m³
general population, inhalative, Acute - systemic effects, 50 mg/m³
Methyl methacrylate, CAS: 80-62-6
Industrial, dermal, Long-term - systemic effects, 13.67 mg/kg bw/d
Industrial, inhalative, Long-term - systemic effects, 208 mg/m³
general population, dermal, Long-term - systemic effects, 8.2 mg/kg bw/d
general population, inhalative, Long-term - systemic effects, 74.3 mg/m³
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m³
Industrial, inhalative, Long-term - local effects, 5.58 mg/m³
Industrial, dermal, Long-term - systemic effects, 970 μg/kg bw/day
general population, oral, Long-term - local effects, 740 μg/kg bw/day
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
Industrial, dermal, Long-term - systemic effects, 970 μg/kg bw/day
Industrial, inhalative, Long-term - local effects, 5.58 mg/m³
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m³
general population, inhalative, Long-term - local effects, 1.19 mg/m³
general population, inhalative, Long-term - systemic effects, 740 μg/kg bw/day
2,6-di-tert-butyl-p-cresol, CAS: 128-37-0
Industrial, dermal, Long-term - systemic effects, 500 μg/kg bw/day
Industrial, inhalative, Long-term - systemic effects, 1.76 mg/m³
general population, oral, Long-term - systemic effects, 250 μg/kg bw/day
general population, dermal, Long-term - systemic effects, 250 μg/kg bw/day
general population, inhalative, Long-term - systemic effects, 435 μg/m³

### **PNEC**

# Substance

Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, <0,03% aromatics, CAS: 1174522-45-2

### Ferdinand Bilstein GmbH + Co. KG

Date printed 16.02.2023, Revision 16.02.2023



Version 12.0. Supersedes version: 11.0 Page 6 / 16

There are no PNEC values established for the substance.	
Methyl methacrylate, CAS: 80-62-6	
sediment (freshwater), 5.74 mg/kg	
sewage treatment plants (STP), 10 mg/L	
seawater, 0.94 mg/L	
freshwater, 0.94 mg/L	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0	
oral (food), 9.33 mg/kg food	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1	
oral (food), 9.33 mg/kg food	
2,6-di-tert-butyl-p-cresol, CAS: 128-37-0	
oral (food), 16.67 mg/kg food	
soil, 53.9 µg/kg soil dw	
sediment (seawater), 45.82 µg/kg sediment dw	
sediment (freshwater), 458.19 µg/kg sediment dw	
sewage treatment plants (STP), 17 μg/L	
seawater, 19.9 ng/L	

# 8.2 Exposure controls

Additional advice on system design 
Ensure adequate ventilation on workstation.

Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

General exposure limit for oil mist should be noted.

**Eye protection** If there is a risk of splashing:

safety glasses (EN 166:2001)

**Hand protection** The details concerned are recommendations. Please contact the glove supplier for further

information.

> 0.4 mm; Nitrile rubber, >480 min (EN 374-1/-2/-3).

> 0.4 mm; Neoprene, >480 min (EN 374-1/-2/-3).

**Skin protection** light protective clothing

freshwater, 199 ng/L

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Avoid contact with eyes and skin.

Respiratory protection Breathing apparatus in the event of aerosol or mist formation.

Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)

Thermal hazards none

Delimitation and monitoring of the

environmental exposition

Comply with applicable environmental regulations limiting discharge to air, water and soil.

# ebi bilstein

### Ferdinand Bilstein GmbH + Co. KG

Date printed 16.02.2023, Revision 16.02.2023

Version 12.0. Supersedes version: 11.0 Page 7 / 16

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Physical stateliquidFormliquidColorgreenOdorcharact

Odor characteristic
Odour threshold not relevant
pH-value not applicable
pH-value [1%] not applicable

**Boiling point [°C]**No information available.

**Flash point [°C]** 160 (ISO 2592)

Flammability (solid, gas) [°C] No information available.

Lower explosion limit No information available.

Upper explosion limit No information available.

Oxidising properties no

Vapour pressure/gas pressure [kPa] No information available.

Density [g/cm³] 0.83 (DIN 51757) (15 °C / 59,0 °F)

Relative density not determined

Bulk density [kg/m³] not applicable

Solubility in water immiscible

Solubility other solvents

Partition coefficient [n-octanol/water]

Kinematic viscosity

Relative vapour density

Evaporation speed

Melting point [°C]

Auto-ignition temperature [°C]

No information available.

9.2 Other information

none

No information available.

### **SECTION 10: Stability and reactivity**

Particle characteristics

### 10.1 Reactivity

No dangerous reactions known if used as directed.

### 10.2 Chemical stability

The product is stable under standard conditions.

# 10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

Reactions with acids.

Reactions with strong alkalies.

# Ferdinand Bilstein GmbH + Co. KG

Date printed 16.02.2023, Revision 16.02.2023



Version 12.0. Supersedes version: 11.0 Page 8 / 16

# 10.4 Conditions to avoid

See SECTION 7.2. Strong heating.

# 10.5 Incompatible materials

Oxidizing agent Strong basic compounds Strong acids.

# 10.6 Hazardous decomposition products

No hazardous decomposition products known.

Date printed 16.02.2023, Revision 16.02.2023



Version 12.0. Supersedes version: 11.0 Page 9 / 16

# **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute oral toxicity

Product

oral, Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6

LD50, oral, Rat, > 5000 mg/kg bw

Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, <0,03% aromatics, CAS: 1174522-45-2

LD50, oral, Rat, >5000 mg/kg bw, OECD 401

1-Decene, Dimer, hydrogenated, CAS: 68649-11-6

LD50, oral, Rat, > 5000 mg/l

Methyl methacrylate, CAS: 80-62-6

LD50, oral, Rat, > 5000 mg/kg OECD 401

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

LD50, oral, Rat, 5000 mg/kg bw

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1

LD50, oral, Rat, 5000 mg/kg bw

2,6-di-tert-butyl-p-cresol, CAS: 128-37-0

LD50, oral, Rat, 2930 - 6000 mg/kg bw

### Acute dermal toxicity

Product

dermal, Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6

LD50, dermal, Rabbit, > 2000 mg/kg bw

Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, <0,03% aromatics, CAS: 1174522-45-2

LD50, dermal, Rabbit, 3160 mg/kg bw

1-Decene, Dimer, hydrogenated, CAS: 68649-11-6

LD50, dermal, Rabbit, > 3000 mg/l

Methyl methacrylate, CAS: 80-62-6

LD50, dermal, Rabbit, > 5000 mg/kg

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

LD50, dermal, Rabbit, 2000 - 5000 mg/kg bw

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1

LD50, dermal, Rabbit, 2000 - 5000 mg/kg bw

2,6-di-tert-butyl-p-cresol, CAS: 128-37-0

LD10, dermal, Rat, 2000 mg/kg bw

### Acute inhalational toxicity

Product

ATE-mix, inhalativ (mist), 1.79 mg/l

Substance

# ebi bilstein

### Ferdinand Bilstein GmbH + Co. KG

Date printed 16.02.2023, Revision 16.02.2023

Version 12.0. Supersedes version: 11.0

Page 10 / 16

Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
LC50, inhalative, Rat, > 5.53 mg/l/4h (dust/mist)
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, <0,03% aromatics, CAS: 1174522-45-2
LC50, inhalative, Rat, >5.266 mg/L
1-Decene, Dimer, hydrogenated, CAS: 68649-11-6
LC50, inhalative, Rat, >1.81 mg/l 4h
Methyl methacrylate, CAS: 80-62-6
LC50, inhalative, Rat, 29.8 mg/l
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h

Serious eye damage/irritation

Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

Eye, non-irritating

Skin corrosion/irritation

Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

dermal, non-irritating

Respiratory or skin sensitisation

Based on the available information, the classification criteria are not fulfilled.

May produce an allergic reaction.

Calculation method

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

dermal, non-sensitizing

Specific target organ toxicity — single exposure

Based on the available information, the classification criteria are not fulfilled.

Specific target organ toxicity — repeated exposure

Based on the available information, the classification criteria are not fulfilled.

e e
Substance
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, <0,03% aromatics, CAS: 1174522-45-2
NOAEL, oral, Rat, 5000 mg/kg bw/day
NOAEC, inhalative, Rat, 10.4 mg/L air
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOAEL, dermal, Rabbit, 1000 mg/kg bw/day
NOAEL, inhalative, Rat, 980 mg/m³ air
LOAEL, oral, Rat, 125 mg/kg bw/day
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
NOAEL, dermal, Rat, 30 - 2000 mg/kg bw/day
NOAEC, inhalative, Rat, 980 mg/m³ air
LOAEL, oral, Rat, 125 mg/kg bw/day
2,6-di-tert-butyl-p-cresol, CAS: 128-37-0
NOAEC, oral, Rat, 25 - 70 mg/kg bw/day

### Ferdinand Bilstein GmbH + Co. KG

Date printed 16.02.2023, Revision 16.02.2023



Version 12.0. Supersedes version: 11.0 Page 11 / 16

Mutagenicity Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

in vitro, negativ

Reproduction toxicity Based on the available information, the classification criteria are not fulfilled.

- Fertility

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

NOAEL, oral, Rat, 1000 mg/kg bw/d, no adverse effect observed

- **Development** No information available.

CarcinogenicityBased on the available information, the classification criteria are not fulfilled.Aspiration hazardBased on the available information, the classification criteria are fulfilled.

On basis of test data

**General remarks** 

Toxicological data of complete product are not available.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.

11.2 Information on other hazards

Endocrine disrupting properties Contains no ingredients with endocrine-disrupting properties.

Other information none

Date printed 16.02.2023, Revision 16.02.2023



Version 12.0. Supersedes version: 11.0 Page 12 / 16

# **SECTION 12: Ecological information**

# 12.1 Toxicity

Substance
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
LC50, (96h), fish, > 100 mg/l
IC50, (48h), Algae, > 100 mg/l
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, <0,03% aromatics, CAS: 1174522-45-2
EC50, (72h), Algae, 10 g/L
NOELR, (21d), Invertebrates, 1 g/L
NOELR, (28d), fish, 1 g/L
LL50, (48h), Invertebrates, 3.193 g/L
LC100, (96h), fish, 1.028 g/L
1-Decene, Dimer, hydrogenated, CAS: 68649-11-6
EC50, (48h), Daphnia magna, > 1000 mg/l
EL50, (72h), Algae, >1000 mg/l
NOELR, (21d), Daphnia magna, 125 mg/l
LL50, (96h), Oncorhynchus mykiss, >1000 mg/l
Methyl methacrylate, CAS: 80-62-6
LC50, (96h), Oncorhynchus mykiss, > 79 mg/l OECD 203
EC50, (72h), Selenastrum capricornutum, > 110 mg/l OECD 201
EC50, (48h), Daphnia magna, 69 mg/l OECD 202
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOELR, (14d), fish, 1 g/L
LL50, (96h), Invertebrates, 10 g/L
LL50, (96h), fish, 100 mg/L
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
NOELR, (14d), fish, 1 g/L
LL50, (4d), fish, 100 mg/L
LL50, (4d), Invertebrates, 10 g/L
2,6-di-tert-butyl-p-cresol, CAS: 128-37-0
LC50, (96h), fish, 199 - 570 μg/L
EC50, (48h), Invertebrates, 480 - 610 μg/L
EC50, (4d), Algae, 758 μg/L
NOEC, (45d), fish, 53 μg/L
NOEC, (21d), Invertebrates, 23 - 316 μg/L

# 12.2 Persistence and degradability

Behaviour in environment

not determined

compartments

Behaviour in sewage plant not determined Biological degradability not determined

# 12.3 Bioaccumulative potential

No information available.

# Ferdinand Bilstein GmbH + Co. KG

Date printed 16.02.2023, Revision 16.02.2023



Version 12.0. Supersedes version: 11.0 Page 13 / 16

### 12.4 Mobility in soil

No information available.

#### 12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

#### 12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

### 12.7 Other adverse effects

Ecological data of complete product are not available.

The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

**Product** 

In according to RoHS!

Coordinate disposal with the disposal contractor/authorities if necessary.

Dispose of as hazardous waste.

Waste no. (recommended)

130206\* 130111\*

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended) 150110\* packaging containing residues of or contaminated by hazardous substances

# **SECTION 14: Transport information**

### 14.1 UN number or ID number

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN) no

not applicable

Marine transport in accordance with

not applicable

IMDG

Air transport in accordance with IATA not applicable

### Ferdinand Bilstein GmbH + Co. KG

Date printed 16.02.2023, Revision 16.02.2023



Page 14 / 16 Version 12.0. Supersedes version: 11.0

14.2 UN proper shipping name

Transport by land according to

ADR/RID

NO DANGEROUS GOODS

Inland navigation (ADN)

NO DANGEROUS GOODS

**IMDG** 

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN)

not applicable

Marine transport in accordance with not applicable

**IMDG** 

Air transport in accordance with IATA not applicable

14.4 Packing group

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN)

not applicable

Marine transport in accordance with not applicable

**IMDG** 

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to

ADR/RID

no

Inland navigation (ADN)

no

Marine transport in accordance with no

**IMDG** 

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

not applicable

14.7 Maritime transport in bulk according to IMO instruments

not applicable

### Ferdinand Bilstein GmbH + Co. KG

Date printed 16.02.2023, Revision 16.02.2023



Version 12.0. Supersedes version: 11.0 Pa

Page 15 / 16

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 2008/98/EC 2000/532/EC); 2010/75/EU; 2004/42/EC; (EC) 648/2004; (EC) 1907/2006

(REACH); (EU) 1272/2008; 75/324/EEC ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131;

(EU) 517/2014

TRANSPORT-REGULATIONS ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2023)

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK

REACH; GB CLP.

- Observe employment restrictions

for people

Observe employment restrictions for mothers-to-be and nursing mothers.

Observe employment restrictions for young people.

- VOC (2010/75/CE) 0 %

### 15.2 Chemical safety assessment

For this product a chemical safety assessment has not been carried out.

### **SECTION 16: Other information**

# 16.1 Hazard statements (SECTION 3)

H317 May cause an allergic skin reaction.

H315 Causes skin irritation.

H335 May cause respiratory irritation. H225 Highly flammable liquid and vapour.

H410 Very toxic to aquatic life with long lasting effects.

H400 Very toxic to aquatic life.

H304 May be fatal if swallowed and enters airways.

H332 Harmful if inhaled.

### Ferdinand Bilstein GmbH + Co. KG

Date printed 16.02.2023, Revision 16.02.2023



Version 12.0. Supersedes version: 11.0 Page 16 / 16

#### 16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

ATE = acute toxicity estimate CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level

EC50 = Median effective concentration

ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

EL50 = Median effective loading

ELINCS = European List of Notified Chemical Substances

EmS = Emergency Schedules

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform ChemicaL Information Database

IVIS = In vitro irritation score

LC50 = Lethal concentration, 50%

LD50 = Median lethal dose

LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

LL50 = Median lethal loading

LQ = Limited Quantities

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value – time-weighted average TLV®STEL = Threshold limit value – short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

# 16.3 Other information

Classification procedure Acute Tox. 4: H332 Harmful if inhaled. (Calculation method)

Asp. Tox. 1: H304 May be fatal if swallowed and enters airways. (On basis of test data) Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects. (Calculation method)

Modified position SECTION 3 been added: Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, <0,03% aromatics

SECTION 3 been added: Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

SECTION 3 been added: Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3%

DMSO Extrakt)

SECTION 3 deleted: Gas oils (petroleum), hydrodesulfurized