
Hankook & Company


한국앤컴퍼니 주식회사


286, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, 13494 Korea


> Type No.: MF57113 Created: 05.02.2022 Modified: 05.02.2022

TECHNICAL DATA SHEET









PERFORMANCE			CONTAINER		
VOLTAGE:	12	V	Group:	LB3	Black
C20:	72	Ah	Hold Down:	B13	
CCA:	640	EN	Please refer to the catalo	og or our website for the deta	ils of hold down
Vibration:	V3		types of the battery container.		
Endurance:	-		COVER		
Water consumption:	W4		Туре:	Heat sealed	Black
Technology:	Flooded		Polarity:	L	
Grid alloy:	Ca/Ca		Terminals:	Standard	
			Filter:	2 Filters both sides	
WEIGHT AND STD. DIMENSION			HANDLES		
Battery weight:	16,4	kg	Handles:	2 handles	
Volume acid:	3,5	1		REMARK	
Length:	277	mm			
Width:	174	mm			
Height:	175	mm			
Total Height:	175	mm			

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by HANKOOK & COMPANY.