


Hankook & Company 한국앤컴퍼니 주식회사 286, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, 13494 Korea


TECHNICAL DATA SHEET

Type No.: MF57412 Created : 05.02.2022 Modified : 05.02.2022









PERFORMANCE			CONTAINER		
VOLTAGE:	12	V	Group:	L3	Black
C20:	74	Ah	Hold Down:	B13	
CCA:	680	EN	Please refer to the catalo	g or our website for the deta	ils of hold down
Vibration:	V3		types of the battery container.		
Endurance:	-		COVER		
Water consumption:	W4		Type:	Heat sealed	Black
Technology:	Flooded		Polarity:	L	
Grid alloy:	Ca/Ca		Terminals:	Standard	
			Filter:	2 Filters both sides	
	ND STD. DIME	NSION		HANDLES	
Battery weight:	17,3		Handles:	2 handles	
Volume acid:	4,2	kg I	nanules.	REMARK	
Length:	4,2	mm			
Width:	174	mm			
Height:	190	mm			
Total Height:	190	mm			
i otari ricigitti	150				
This document includes confidential data, is not contractual and could be changed without notice. Any use, conv.or distribution has to be authorised in					

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by HANKOOK & COMPANY.