
한국앤컴퍼니 주식회사


286, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, 13494 Korea


> Type No.: MF59519 Created: 05.02.2022 Modified: 05.02.2022

TECHNICAL DATA SHEET









PERFORMANCE				CONTAINER		
VOLTAGE:	12	V	Group:	D31(27)	Black	
C20:	95	Ah	Hold Down:	B1		
CCA:	720	EN	Please refer to the cata	log or our website for the det	ails of hold down	
Vibration:	V3		types of the battery cor	types of the battery container.		
Endurance:	-			COVER		
Water consumption:	W4		Type:	Heat sealed	Black	
Technology:	Flooded		Polarity:	R		
Grid alloy:	Ca/Ca		Terminals:	Standard		
			Filter:	2 Filters both sides		
WEIGHT AND STD. DIMENSION				HANDLES		
Battery weight:	21,6	kg	Handles:	1 handle		
Volume acid:	5,4	1		REMARK		
Length:	302	mm				
Width:	172	mm				
Height:	220	mm				
Total Height:	220	mm				

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by HANKOOK & COMPANY.