

## Hankook & Company


한국앤컴퍼니 주식회사 286, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, 13494 Korea


## **TECHNICAL DATA SHEET**

Type No.: PMF55205 Created : 05.02.2022 Modified : 05.02.2022









PERFORMANCE				CONTAINER		
VOLTAGE:	12	V	Group:	LB1	L.Gray	
C20:	52	Ah	Hold Down:	B13		
CCA:	520	EN	Please refer to the cata	Please refer to the catalog or our website for the details of hold down		
Vibration:	V3		types of the battery cor	types of the battery container.		
Endurance:	E1			COVER		
Water consumption:	W4		Type:	Heat sealed	L.Gray	
Technology:	Flooded		Polarity:	L		
Grid alloy:	Ca/Ca		Terminals:	Standard		
			Filter:	2 Filters both sides		
WEIGHT AND STD. DIMENSION				HANDLES		
Battery weight:	12,1	kg	Handles:	1 handle		
Volume acid:	2,8	1		REMARK		
Length:	208	mm				
Width:	174	mm				
Height:	174	mm				
Total Height:	174	mm				

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by HANKOOK & COMPANY.