

Hankook & Company


한국앤컴퍼니 주식회사 286, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, 13494 Korea


TECHNICAL DATA SHEET

Type No.: PMF57705 Created : 05.02.2022 Modified : 05.02.2022









PERFORMANCE			CONTAINER		
VOLTAGE:	12	V	Group:	L3	L.Gray
C20:	77	Ah	Hold Down:	B13	
CCA:	780	EN	Please refer to the catalog or our website for the details of hold down		
Vibration:	V3		types of the battery container.		
Endurance:	E1		COVER		
Water consumption:	W4		Туре:	Heat sealed	L.Gray
Technology:	Flooded		Polarity:	L	
Grid alloy:	Ca/Ca		Terminals:	Standard	
			Filter:	2 Filters both sides	
WEIGHT A	ND STD. DIME	NSION		HANDLES	
Battery weight:	18,5	kg	Handles:	2 handles	
Volume acid:	4,1	I		REMARK	
Length:	277	mm			
Width:	174	mm			
Height:	190	mm			
Total Height:	190	mm			
This document includes config					

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by HANKOOK & COMPANY.