

## Hankook & Company


## **TECHNICAL DATA SHEET**


한국앤컴퍼니 주식회사 286, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, 13494 Korea

> Type No.: PMF58005 Created : 05.02.2022 Modified : 05.02.2022









PE	RFORMANCE		CONTAINER
VOLTAGE:	12	V	Group: LB4 L.Gray
C20:	80	Ah	Hold Down: B13
CCA:	800	EN	Please refer to the catalog or our website for the details of hold down
Vibration:	V3		types of the battery container.
Endurance:	E1		COVER
Water consumption:	W4		Type: Heat sealed L.Gray
Technology:	Flooded		Polarity:
Grid alloy:	Ca/Ca		Terminals: Standard
			Filter: 2 Filters both sides
WEIGHT A	ND STD. DIME		HANDLES
Battery weight:	19,2	kg	Handles: 2 handles
Volume acid:	4,6	l	REMARK
Length:	315	mm	
Width:	174	mm	
Height:	175	mm	
Total Height:	175	mm	
			d be changed without patice. Any use, cany or distribution bas to be authorized

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by HANKOOK & COMPANY.