

한국앤컴퍼니 주식회사


286, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, 13494 Korea


> Type No.: SHD 68032 Created: 05.02.2022 Modified: 05.02.2022

TECHNICAL DATA SHEET









PERFORMANCE			CONTAINER		
VOLTAGE:	12	V	Group:	EN B	L.Gray
C20:	180	Ah	Hold Down:	B0/B13	
CCA:	1000	EN	Please refer to the catalog or our website for the details of hold down		
Vibration:	V3		types of the battery container.		
Endurance:	-		COVER		
Water consumption:	W4		Туре:	Heat sealed	L.Gray
Technology:	Flooded		Polarity:	R	
Grid alloy:	Ca/Ca		Terminals:	Standard	
			Filter:	2 Filters both sides	
WEIGHT AND STD. DIMENSION			HANDLES		
Battery weight:	44,7	kg	Handles:	2 handles	
Volume acid:	10,9	1		REMARK	
Length:	511	mm			
Width:	222	mm			
Height:	217	mm			
Total Height:	217	mm			

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by HANKOOK & COMPANY.