



## THE NETHERLANDS



## EEC TYPE-APPROVAL CERTIFICATE

Communication concerning the:

- type-approval
- ~~extension of type approval~~
- ~~refusal of type approval~~
- ~~withdrawal of type approval~~

of a type of a component (towbar) with regard to Directive (94/20/EEC)

**Type-approval number: e4\*94/20\*1140\*00**

Reason for extension:

## SECTION I

- |        |  |  |
|--------|--|--|
| 0.1    | Make (trade name of manufacturer)  | : Le Rapide  |
| 0.2.   | Type and general commercial description(s)   | : 023471   |
| 0.3.   | Means of identification of type marked on the component  | : Approval number  |
| 0.3.1. | Location of the marking  | : on type plate  |
| 0.5.   | Name and address of manufacturer   | : Bosal Le Rapide<br>Rue de Reims<br>F-51490 Beine Nauroy France |
| 0.7.   | In the case of components and separate technical units, location and method of affixing of the EEC approval mark | : on type plate  |
| 0.8.   | Name(s) and address(es) of assembly plants   | : See information document<br>(annex III, item 0.8)              |

SECTION II

1. Additional information (where applicable) : see Appendix I
2. Technical service responsible for carrying out the tests : RDW  
Testbaan|Centrum  
Talingweg 76  
8218 NX Lelystad
3. Date of testreport : 15-02-1999
4. Number of testreport : RDW-94/20-0185
5. Remarks (if any) : see Appendix I
6. Place : Zoetermeer
7. Date : 23-02-1999
8. Signature :



9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request, is attached.

- Application form relating to annex III and annexed drawings
- Drawings and instructions for attachment
- Fitting instructions
- Test report as mentioned in item 4.

**Appendix I**  
**to EEC type-approval certificate No : e4\*94/20\*1140\*00**  
**concerning the components type-approval of mechanical coupling devices with regard to**  
**Directive 94/20/EEC**

- |      |   |   |     |
|------|---|---|-----|
| 1.   | Additional information  |   |     |
| 1.1. | Class of the type of coupling   | : A50-X   |     |
| 1.2. | Categories or types of vehicles for which the device is designed or restricted  | : see fitting instructions  |     |
| 1.3. | Maximum D-value   | : 15,85   | kN  |
| 1.4. | Maximum vertical load S at the coupling point   | : 100   | kg  |
| 1.5. | Maximum load U at the fifth wheel coupling point  | : -----   | ton |
| 1.6. | Maximum V-value   | : -----   | kN  |
| 1.7. | Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fitting points at the vehicle given by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles | : see fitting instructions  |     |
| 1.8. | Information on the fitting of special towing brackets or mounting plates  | : see fitting instructions  |     |
| 5.   | Remarks   | : The installation of the coupling device to the vehicle must be checked according to requirements of Annex VII, see Annex I, par.5.10. |     |